

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Page(s) 4241)

Set granite stone, 5x12x18" 12" in the ground for the 1/4 sec. cor. marked 1/4 on W face; from which
A cedar, 12" dia., bears N.72°E., 22 lks., mkd: 1/4 S21 BT.
A fir, 24" dia., bears S.86°W., 15 lks., mkd: 1/4 S20 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4331)

Intersect the 1/4 cor of secs. 20 & 21, established by Deputy Gibb in 1909, which is a granite stone, 6x12x5" above ground, firmly set, marked & witnessed as described by the surveyor general.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - Aug 1967 - C.S. File 54/40-74

We chain south from closing corner of secs. 20 & 21, 414.0 ft. to exact point for 1/4 corner as determined by orig. BTs:
Orig. 12" cedar, now 16" sawed stump under logs, one of which is other orig. BT. N.72°E., 14.5 ft., show frag. scribe marks on decayed blaze.
Orig. 24" fir now 30", down & out of position, S.86°W., 9.9 ft., open blaze & find "1/4 S20" under 45+ years of overgrowth.

Mensch's rec. dist. between CC & 1/4 corner is 417.8 ft.
Set - Brass cap at cor. mkd: COUNTY SURVEYOR T26S R2W
OFFICE 1967 1/4 S 20|S 21
New BTs- 9" W.Fir S.43°W., 24.5 ft. mkd: 1/4 S20 CS BT
8" Hemlock S.44°E., 40.9 ft. mkd: 1/4 S21 CS BT
Found no trace of orig. corner stone. Corner lies in center of old cat skid road.

Fd. BC & 2 BTs by D. Edwards, 4/2008 - M155-46