

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 300346

PRIMARY CORNER DESCRIPTION CC Secs. 20 & 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Page(s) 4241)  
-----  
Set granite stone, 8x10x14", 10" in the ground for closing cor. secs. 20 & 21, marked CC on S face, with 4 grooves on E & 2 grooves on W face, from which  
    A fir, 36" dia. bears S.21°W. 24 lks. mkd: T26S R2W S20 BT  
    A fir, 24" dia. bears S.31°E. 54 lks. mkd: T26S R2W S21 BT

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4332)  
-----  
Intersect old S bdy of sec. 17 & S bdy of Tract No. 37 S.89°52'E., 6.50 chs. from cor. No. 4.  
At the point of intersection  
Set an iron post, 3' long, 2" dia., 24" in the ground, for closing cor. of secs. 20 & 21, with brass cap marked:  
                  T26S R2W  
                    S 17    
                  S 20 | S 21  
                  T26S | R2W  
                  CC  
                  1916  
from which  
    A fir, 40" dia. bears S.46°E. 52 lks. mkd: T26S R2W S21 BT  
    A fir, 50" dia. bears S.10°W. 16 lks. mkd: T26S R2W S20 BT  
The cor. established by Deputy Gibb in 1909 as the closing cor. of secs. 20 & 21, which is a granite stone, 4x10x8" above ground, firmly set, marked & witnessed as described by the surveyor general, bears N.29°E., 10 lks. dist.

FD. Mensch BC, by G Lang, 11/2013 - C.S. file 65/79-17