

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4317, 4323 & 4338)

Page 4317

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 16 & 17, with brass cap mkd:

T26S R2W
S 17|S 16
1918

from which

A fir, 30" dia. bears N.69°E. 47 lks. mkd: T26S R2W S16 BT

A fir, 24" dia., bears N.39°W., 103 lks., mkd: T26S R2W S17 BT.

Page 4323

The orig. McQuinn cor. of secs. 16, 17, 20, & 21, identified by Gibb & re-established by me in 1916 bears S.50°08'E., 37.64 chs. I destroy marks on iron post.

Page 4338

Intersect cor. of secs. 16 & 17, heretofore described. I now place additional marks on the iron post to designate it as cor. No. 3 of Tract No. 37. The post is now mkd:

T26S R2W **3 TR 37**
S 17|S 16
1918

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12736)

The SE cor. of sec. 17, which is also cor. No. 3 of Tract 37, monumented by Mensch in 1918 with an iron post, 2" dia., protruding 8" above ground, firmly set in a mound of stone, 2½ ft. base, 1 ft. high, with brass cap properly mkd., from which 1918 BTs

A sawed fir stump, 40" dia., bears N.69°E., 47 lks., with a healed blaze.

A fir snag, 24" dia., bears N.39°W., 103 lks., with scribe marks T 7 visible on a partially opened blaze.

add 2 new BTs

A fir, 6" dia. bears N.85°E., 24 lks. mkd: T26S R2W S16 BT

A fir, 8" dia. bears N.73°W., 50 lks. mkd: T26S R2W S17 BT

FD. Mensch BC, by G Lang, 11/2013 - C.S. file 65/79-17