

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor Secs 8, 9, 16, & 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4211-2)

-----  
Set post, 4 ft. long, 4" sq., 24" in the ground for cor. of secs. 8, 9, 16, & 17, mkd T26S S9 on NE, R2W S16 on SE, S17 on SW & S8 on NW faces with 3 notches on S and 4 notches on E edges, from which  
A fir, 48" dia. bears N.40°E., 28 lks. mkd: T26S R2W S9 BT  
A fir, 24" dia. bears S.15°E. 10 lks. mkd: T26S R2W S16 BT  
A fir, 20" dia. bears S.55°W. 42 lks. mkd: T26S R2W S17 BT  
A fir, 14" dia. bears N.83°W., 43 lks. mkd: T26S R2W S8 BT

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4316)

-----  
The cor. of secs. 8, 9, 16, & 17 which I verify as the orig. McQuinn cor. The old cor., a post, has been replaced by a stake and the old post is not found. The cor. point is witnessed as described by the surveyor general. I perpetuate this cor. by setting an iron post, 3 ft. long, 2" dia., 24" dia., in the ground, for cor. of secs. 8, 9, 16, & 17, with brass cap marked:  
T26S R2W  
S 8 | S 9  
S 17 | S 16  
1918

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12738)

-----  
The cor. of secs. 8, 9, 16, & 17, remonumented by Mensch in 1918, with an iron post, 2" dia., firmly set, protruding 8" above ground, with brass cap (properly) mkd from which the remaining 1883 BTs  
A fir, 56" dia., bears N.40°E., 28 lks., with illegible scribe marks on bark.  
A fir, 36" dia., bears S.20°E., 10 lks., with old axe marks visible on the bark. (Rec. bearing S.15°E.)  
A fir 40" dia., bears S.55°W., 39 lks., with old axe marks visible on bark. (Rec. dist. 42 lks.)  
add one new BT  
A chinquapin, 10" dia., bears N.75¼°W., 16 lks., mkd: T26S R2W S8 BT.

continued next page

1

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor Secs 8, 9, 16, & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ken Hoffine - For: Lone Rock Management Co. - 5/2016 - M172-7  
-----

Found - 1918 USGLO brass cap 1.0 ft above ground.  
67" D.Fir bears N.41°E., 19.4 ft (record N.40°E.,  
18.48 ft) healed face and BLM tag  
38" D.Fir bears S.20¼°E., 7.7 ft (record S.20°E. 6.6  
ft) healed face and BLM tag.  
53" D.Fir bears S.54°W., 25.4 ft (record S.55°W.,  
25.74 ft) healed face and BLM tag.  
14" chinquapin bears N.74¼°W., 10.55 ft (record  
N.75¼°W., 10.56 ft) healed face and BLM tag  
Corner lies on east facing slope in heavy huckleberry brush.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral  
Surveyor, under Group No. 2923, surveyed July 2018/March  
2020- (DCSO records Vol. 59 Pages 24059)  
-----

The cor. of secs. 8, 9, 16, and 17, reported by Zirpel, Jr.,  
and Glenn in 1959, monumented with an iron post, 2" dia.,  
firmly set, projecting 13" above ground, with a brass cap  
(properly) mkd.  
from which the remains of the BTs reported by Zirpel, Jr.,  
and Glenn

A fir, 64" dia., bears N.40°E., 18.5 ft., with illegible  
scribe marks visible on bark. (Original)

A fir, 37" dia., bears S.20°E., 6.6 ft., no marks visible.  
(Original)

A fir, 51" dia., bears S.55°W., 25.7 ft., no marks  
visible. (Original)

A chinquapin snag, 14" dia., bears N.75¼°W., 10.6 ft.,  
with a healed blaze.

and a new bearing tree

An alder, 5" dia., bears N.64¼°W., 34.8 ft., mkd. T26S R2W  
S8 BT on bark.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at  
the base right side-center & each monument established or  
remonumented has a magnet deposited in a white plastic case  
at the base of the stainless steel post. Alum. Angle iron  
driven alongside each monument unless a similar marker was  
already in place.

NAD 1983 (2011)

Latitude: 43°18'47.75" N. Longitude: 122°57'05.53" W.