TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4213)

Set fir post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on W face, from which
A fir, 18" dia., bears S.61°E., 15 lks., mkd: ¼ S BT.
A fir, 18" dia., bears N.50°W., 8 lks., mkd: ¼ S BT.

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12741)

Point for the ¼ sec. cor. of secs. 8 & 9, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground with brass cap marked: T26S R2W

¼
S 8|S 9
1959

from which
A fir, 11" dia., bears N.75°E., 29 lks., mkd: ¼ S9 BT.
A fir, 20" dia., bears N.70°W., 44½ lks., mkd: ¼ S8 BT.

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #990, surveyed Aug/Sept 1979 - (DCSO records Vol. 44 Page(s) 16945)

The ¼ sec. cor. of secs. 8 & 9, monumented with an iron post, 2½" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd.
from which BTs mkd. by Zirpel & Glenn
A fir, 12" dia., bears N.75°E., 29 lks. with healed blaze.
A fir, 20" dia. bears N.70°W., 44½ lks. with healed blaze.
Cor. is located on NE cor. of logged area, edge bears S & W.

Ken Hoffine - For: Lone Rock Management Co. - 5/2016 - M172-7

Found - 1959 BLM brass cap 0.8 ft above ground.
12" D.Fir bears N.77°E., 17.9 ft (record N.75°E., 19.14 feet) healed face and BLM tag.
36" D.Fir bears N.68¼°W., 29.9 feet (record N.70°W., 29.37 feet) healed face and BLM tag.
Corner lies on north facing slope in mound of stones.