

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor Secs 4, 5, 8, & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4213)

-----

Set a post, 4 ft. long, 4" square, 24" in the ground, for cor. to secs. 4, 5, 8 & 9, marked T26S S4 on NE, R2W S9 on SE, S8 on SW, & S5 on NW faces, with 5 notches on S & 4 on E edges; from which

- A fir, 36" dia., bears N.10°E., 56 lks., mkd: T26S R2W S4 BT.
- A laurel, 10" dia., bears S.60°E., 45 lks., mkd: T26S R2W S9 BT.
- A fir, 48" dia., bears S.50°W., 19 lks., mkd: T26S R2W S8 BT.
- A laurel, 12" dia., bears N.40°W., 100 lks., mkd: T26S R2W S5 BT.

Lester E. Calder, Weyerhaeuser Timber Co. - 3/1957 - C.S. 40/399

-----

Corner established by double proportionate method.

Set a 2½" sq. stake at corner point, from which

- 34" Fir, N.17°E., 26.9 ft. (Note: This work done
- 32" Fir, N.55°W., 36.7 ft. a staff compass &
- 10" Fir, S.8°W., 12.2 ft. abney slope chain)
- 20" Fir, S.42½°E., 37.1 ft.

The above trees referenced by the Weyerhaeuser method - a 4.7"x5.7" aluminum plate with embossed section plat nailed head high on the tree. Near base of tree a notch is cut & a square headed nail with "W" on head driven through a hole in a 2½" brass disc stamped with the Oregon Registered Land Surveyor or Professional Engineer registration number. The dist. & bearing stamped on aluminum plate refer to the "W" nail.

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12741-2)

-----

The cor. of secs. 4, 5, 8, & 9, reestablished and recorded by Weyerhaeuser Timber Co., in 1952, determined by double proportionate measurement, monumented with a wooden stake, 2" sq. protruding 40" above ground, firmly set, from which 1952 bearing trees:

- A fir, 36" dia., bears N.16½°E., 46 lks., mkd. with a nail stamped W on head and driven through the center of a 3" bronze disc mkd. Registered Engineer No. 2149.

continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor Secs 4, 5, 8, & 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A fir, 17" dia., bears S.42½°E., 57½ lks., mkd. with a nail stamped W on head and driven through the center of a 3" bronze disc. mkd. Registered Engineer No. 2149.

A fir, 8", dia., bears S.9¼°W., 19½ lks., mkd. with a nail stamped W on head and driven through the center of a 3" bronze disc mkd. Registered Engineer No. 2149.

A fir, 27" diam., bears N.55¼°W., 57 lks., mkd. with a nail stamped W on head and driven through the center of a 3" bronze disc. mkd. Registered Engineer No. 2149.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked:

T26S R2W  
S 5 | S 4  
S 8 | S 9  
1959

from which new BTs

A fir, 32" dia., bears N.43¾°E., 65½ lks., mkd: T26S R2W S4 BT.

A fir, 29" dia., bears S.20½°E., 56½ lks., mkd: T26S R2W S9 BT.

A fir, 9" dia., bears S.57¼°W., 34 lks mkd: T26S R2W S8 BT

A fir, 21" dia., bears N.83½°E., 63½ lks., mkd: T26S R2W S5 BT.

Reset the wooden stake alongside the iron post.

Ken Hoffine - For: Lone Rock - Aug. 2017 - C.S. File 65/97-1

Found - 1959 BLM brass cap 36" fir bears N.43¾°E., 43.2 ft. as per record healed face and tag.

33" Fir bears S.20½°E., 37.3 ft. as per record healed face and tag.

16" Fir bears S.57¼°W., 22.4 ft. as per record healed face and tag.

28" Fir bears N.83½°E., 41.9 ft. as per record healed face and tag.

Corner lies on southwest slope and southwesterly of large barren rock area.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24059-60)

The cor. of secs. 4, 5, 8, & 9, reported by Zirpel & Glenn in 1959, monumented with an iron post, 2½" dia., firmly set, projecting 18" above ground, in a mound of stone, 3 ft. base, to the top, with a brass cap (properly) mkd. from which the remains of the BTs reported by Zirpel & Glenn cont. next pg

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor Secs 4, 5, 8, & 9

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

A decayed fir stump, 39" dia., bears N.16½°E., 28.2 ft., with a healed blaze. (Record, 30.4 ft.)  
A decayed fir stump, 31" dia., bears N.43¾°E., 43.2 ft., with scribe marks T26S R2W S4 visible on open blaze.  
A fir, 27" dia. bears S.42½°E., 36.6 ft., with a healed blaze. (Record, 38.0 ft.)  
A fir, 37" dia., bears S.20½°E., 37.3 ft., with a healed blaze.  
A fir, 20" dia., bears S.9¼°W., 12.9 ft., no marks visible.  
A fir, 18" dia., bears S.57¼°W., 22.4 ft., with a healed double blaze.  
A fir, 30" dia., bears N.83½°W., 41.9 ft., with a healed blaze.  
and a new bearing tree  
A madrone, 12" dia., bears N.61¼°E., 6.9 ft., mkd. T26S R2W S4 BT on bark.  
NAD 1983 (2011)  
Latitude: 43°19'43.09" N. Longitude: 122°57'04.25" W.

Ron Quimby - Crew: N. Fromdahl, L. Heddens & J. Ogden - 10/2020 - C.S. File 65/106-55  
-----  
Found - 1959 BLM brass cap (properly marked)  
36" burnt fir N.43¾°E., 43.2 healed scar  
33" burnt fir S.20½°E., 37.3 healed scar  
16" burnt fir S.57¼°W., 22.4 healed scar  
28" burnt stump N.83½°E., 41.9 healed scar  
New - 5/8"x30" I.Rods with yellow plastic cap stamped "ie ENGINEERING" with post alongside:  
N.65°E., 5.2 ft S.65°E., 11.9 ft.  
S.32°E., 10.1 ft. S.54°W., 5.8 ft.  
Note- Area badly burnt 9/2020  
Compass decl. 15½°E.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 1/31/2023 - C.S. File 67/55-30  
-----  
Found - 1959 BLM brass cap, proj 16", in rough stone mound.  
Burnt, dead, 36" Fir N.43¾°E., 43.2 ft. healed scar.  
Burnt, dead, 33" Fir S.20½°E., 37.3 ft. healed scar.  
Burnt, dead, 16" Fir S.57¼°W., 22.4 ft. healed scar.  
Badly burnt 28" Fir stump, N.83½°E., 41.9 ft healed scar.  
5/8"x30" iron rods with yellow plastic cap stamped "ie engineering" with alum. post alongside:  
N.65°E., 5.2 ft S.65°E., 11.9 ft.  
S.32°E., 10.1 ft. S.54°W., 5.8 ft. Cont.

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor Secs 4, 5, 8, & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Note - Area badly burnt 9/2020  
Compass decl. 15½°E.  
Lat: 43°19'43.09" N. Long: 122°57'04.25" W.