

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5 only, (North)

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GL0 survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 9 Page(s) 3582)

Set Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 4, 5, 32 and 33, mkd. T25S S33 on NE.; R2W S4 on SE.; T26S S5 on SW.; and S32 on NW. faces, with 4 notches on E. and 2 notches on W. edges, from which
A Fir 24" dia., bears N.65°E., 28 lks. dist. mkd. T25S R2W S33 BT.
A Fir 24" dia., bears S.10°E., 22 lks. dist. mkd. T26S R2W S4 BT.
A Fir 18" dia., bears S.20°W., 27 lks. dist. mkd. T26S R2W S5 BT.
A Fir 36" dia., bears N.55°W., 5 lks. dist. mkd. T25S R2W S32 BT.

GL0 survey by C.M. Collier, Deputy Surveyor, under Instructions dated May/Sept. 1913 - (DCSO records Vol. 10 Page(s) 4272)

The cor. for 4 & 5, which is a post marked and witnessed as described by the surveyor general. The post being nearly decayed and the Fir bearing tree, 18" dia., S.20°W., 27 lks., being dead and broken, I destroy this cor. and re-establish it in the same place, as follows:
Set a Dogwood post 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 4 & 5, mkd. T26S S4 on SE.; and R2W S5 on SW. face, with 4 notches on E. and 2 notches on W. edges; from which:
A Fir 24" dia., bears N.65°E., 28 lks. dist. mkd. T25S R2W S33 BT. (Orig. BT)
A Fir 24" dia., bears S.10°E., 22 lks. dist. mkd. T26S R2W S4 BT. (orig. BT)
A Yew 6" dia., bears S.60°W., 51 lks. dist. mkd. T26S R2W S5 BT.
A Fir 36" dia., bears N.55°W., 5 lks. dist. mkd. T25S R2W S32 BT.

BLM Resurvey by Irving Zirpel & Wm. Glenn Under Group #404, Surveyed May/Oct. 1959 - (DCSO records Vol. 30 Page(s) 12720-21)

The sec. cor., determined at record brg. and dist. from three remaining bearing trees and a bearing tree established in 1913:

(Cont. Next Page)

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5 only, (North)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

- A Fir 30" dia., bears N.65°E., 28 lks. dist. with illegible bark scribe marks visible.
- A Fir 25" dia., bears S.10°E., 22 lks. dist. bark scribed T26 4 BT and other illegible scribe marks.
- A Yew 10" dia., bears S.60°W., 51 lks. dist. mkd. T26S R2W S5 BT on partially healed blaze. (1913 BT)
- A Fir 38" dia., bears N.55°W., 5 lks. dist. bark scribed 2 R2 6 together with other illegible scribe marks.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:

T 25 S R 2 W
 S 33
 S 5 | S 4
T 26 S R 2 W
1959

BLM Resurvey by Daniel Berry; Harvey Wofford; G. Steven Popken, Cadastral Surveyors, under Group #'s 786, 848 and 854. And Glenn S. Baughman, L.S. #536, under Contract #52500-CT5-1116, Surveyed July 1972/Oct. 1975 - (DCSO records Vol. 36 Page(s) 15103-04)

The Sec. Cor., monumented with an iron post 2½" dia., firmly set, protruding 4" above ground, with brass cap mkd. as in 1959

from which the remains of the original bearing trees:

- A Fir 34" dia., bears N.65°E., 28 lks. dist. with illegible scribe marks visible on bark.
- A sawed Fir stump 25" dia., bears S.10°E., 22 lks. dist., no marks visible.
- A Fir 40" dia., bears N.55°W., 5 lks. dist. with scribe marks 2 R2 6 visible on bark blaze.

and a bearing tree mkd. by Collier in 1913:

- A partially uprooted Yew, 12" dia., bears S.60°W., 51 lks. dist. mkd. T26S R2W S5 BT on partially healed blaze.

and new bearing trees:

- A Cedar 8" dia., bears S.13°E., 89 lks. dist. mkd. T26S R2W S5 BT.
- A Cedar 7" dia., bears S.24°W., 59 lks. dist. mkd. T26S R2W S5 BT.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2919, surveyed May 2018/July 2020 - Approved 3/2021 (DCSO records Vol. 59 Page(s) 23913-4)

The cor. of secs. 4 & 5 only, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd. Continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5 only, (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the original bearing trees
A fir, 39" dia., bears N.65°E., 18.5 ft., with a healed blaze.
A tin-capped, decayed fir stump, 25" dia., bears S.10°E., 14.5 ft. with axe marks visible.
A tin-capped, decayed fir stump, 40" dia., bears N.55°W., 3.3 ft., with a healed blaze.
and the remains of a bearing tree mkd. by Collier in 1913-14
A roothole bears S.60°W., 33.7 ft., alongside of which is a down decayed yew, 12" dia., with a healed blaze.
and the remains of the BTs mkd. by Berry, Wofford, Popken, and Baughman in 1972-75
A cedar snag, 9" dia., bears S.10¼°E., 57.0 ft., with illegible scribe marks visible on partially healed blaze. (Record, S.13°E., 58.7 ft.)
A cedar snag, 7" dia., bears S.24°W., 38.9 ft., with scribe marks T26S R2W S5 BT visible on partially healed blaze.
and new bearing trees
A hemlock, 9" dia., bears S.77½°E., 25.6 ft., mkd. T26S R2W S4 BT.
A fir, 6" dia., bears S.45¼°W., 5.9 ft. mkd T26S R2W S5 BT
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.

Fd. & used on BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24060-1)

Ron Quimby - Crew: N. Fromdahl & J. Ogden - 10/2020 - C.S. File 65/106-56

Found - 1959 BLM brass cap (properly marked)
36" brunt fir N.65°E., 18.5 ft.
27" burnt fir stump S.10°E., 14.5 ft.
42" burnt fir stump N.55°W., 3.3 ft.
18" burnt fir snag S.13°E., 58.7 ft.
Burnt cedar S.24°W., 38.9 ft. size undeterminable.
New - 5/8"x30" I.Rods with yellow plastic cap stamped "ie ENGINEERING" with post alongside:
N.56°E., 9.1' S.80°E., 7.5'
S.6°E., 7.2' S.45°W., 6.4'
Note - Area badly burnt 9/2020
Compass decl. 15½°E.

