

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 323346

PRIMARY CORNER DESCRIPTION AP South line Tract 37 (Cor # 5)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4210-1)

Set hemlock post, 4 ft. long, 4" sq., 24" in the ground for cor. of secs. 16, 17, 20, & 21, mkd T26S S16 on NE, R2W S21 on SE, S20 on SW & S17 on NW faces with 4 notches on E and 3 notches on S edges, from which

- A fir, 18" dia. bears N.55°E. 21 lks. mkd: T26S R2W S16 BT
- A hemlock, 18" dia., bears S.35°E., 35 lks., mkd: T26S R2W S21 BT.
- A hemlock, 18" dia., bears S.35°E*., 35 lks. mkd: T26S R2W S20 BT.
- A hemlock, 12" dia., bears N.10°W., 17 lks., mkd: T26S R2W S17 BT.

*Checked orig notes and the bearing of the Sec. 20 is SE in them 12/31/2007 - DCSO, JC.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4339)

Intersect old McQuinn cor. of secs. 16, 17, 20 & 21, reestablished by me in 1916. Marks on post now destroyed. I re-mark this post to designate it as cor. No. 5 of Tract 37, as follows:

5 TR 37

FD. 24" hemlock BT with vis. scribe N.29°W., 11.2' from Mensch BC, by G Lang, 11/2013 - C.S. file 65/79-17