

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 33; & S 4, T27-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882
- (DCSO records Vol. 10 Page(s) 4182-83)

Set Cedar post 3 ft. long, 3" sq., 24" in the ground for ¼
sec. cor. marked ¼ S on N. & S. faces, from which
A Cedar 20" dia., bears S.57°W., 28 lks. dist. mkd. ¼ S BT
A Fir 36" dia., bears N.55°E., 28 lks. dist. mkd. ¼ S BT.

Cor. Fd. and tied in GLO survey by C.M. Collier, Deputy
Surveyor, under Instructions dated May/Sept. 1913 - (DCSO
records Vol. 10 Page(s) 4260)

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
July 1967 - C.S. File 54/40-35

Found - Orig. 20" now 38" Cedar snag, S.53°W., 18.5 ft. (not
S.57°W.) scribe visible on opened blaze.
Orig. 36" now 48" Fir, N.55°E., 18.5 ft., alive,
bark scribe, poor.

Set Brass cap at cor. mkd: County Surveyors Office
¼ S 33 T26S
S 4 T27S R2W
1967

New BTs- 8" W.Fir N.45°E., 4.8 ft. mkd. ¼ S33 CS BT.
9" W.Fir S.56°W., 43.1 ft. mkd. ¼ S4 CS BT.
Corner lies old E-W cutting line, selective logged to South.

David Edwards - For: Roseburg Resources - 3/2001 - M 136-69
& C.S. File 65/34-5 A & B

Found - Brass cap.
15" dia., Fir bears S.56°W., 43.1 ft.
10" dia., Fir snag bears N.45°E., 4.8 ft.
New BT - 9" dia., Fir bears N.7°E., 12.00 ft.