

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Page(s) 4238)

Set post, 3 ft. long, & 5" sq., 24" in the ground for the ¼ sec. cor. marked ¼ S28 on N and 33 on S face, from which:
 A hemlock, 8" dia., bears S.33°E., 6 lks., mkd: ¼ S33 BT.
 A hemlock, 10" dia., bears N.18°W., 37 lks., mkd: ¼ S28 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - July 1967 - C.S. File 54/40-21

Found very old 5" square cedar post at ¼ S28/S33 & faced to bear S.20°W., instead of S.18°E., from tree to cor. No scribe on axe blaze., proper age to be BT. A hole where tree stood - now gone bears S.33°W., 4.0 ft. instead of S.33°E.

David Edwards - For: Seneca Jones Co. - July 1999 - C.S. File 65/25-4

Set - 5/8"x30" steel pin w/red plastic cap mkd: "D.A. Edwards - LS 2339"
 16" Fir bears N.2°E., 9.98 ft.
 10" Fir bears N.63°E., 20.30 ft.
 14" Fir bears S.36°E., 8.80 ft.
 14" Fir bears S.64°W., 29.35 ft.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2331, Surveyed April/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22930)

The ¼ sec cor of secs. 28 & 33 reestablished by proportionate measurement by Edwards, in 1999; there is no remaining evidence of the original cor. and this position is accepted as a careful and faithful reestablishment of the cor.; monumented with a rebar, 5/8" dia., firmly set, projecting 8" above ground, with a red plastic cap mkd. D.A. Edwards LS 2339, from which the remains of the BTs mkd. by Edwards
 A fir stump, 18" dia., 5½ ft. high, bears N.4¾°E., 10.0 ft., with a healed blaze.
 A fir, 12" dia., bears N.64°E., 20.4 ft., with a healed blaze.
 A fir snag, 15" dia., bears S.33°E., 8.8 ft., with scribe marks ¼ S33 BT visible on an open blaze.
 A fir, 18" dia., bears S.64°W., 29.4 ft., with a healed blaze.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, with brass cap (properly) mkd. continued next pg

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Place the rebar, 30" long, inside the stainless steel post,
and deposit a magnet in a white plastic case at the base.

From the cor. S.89°39'14"E., at:
245 ft., draw, drains N.20°E.
810 ft., spur, slopes N.5°E.
1360 ft., ravine, drains N.35°E.