

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 340520

PRIMARY CORNER DESCRIPTION C S 1/16 Sec 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #990, surveyed Aug/Sept 1979 - (DCSO records Vol. 44 Page(s) 16943)

Point for the center S 1/16 sec. cor. of sec, 9,
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

C
S 1/16 | S 9
C
1979

from which
A fir, 18" dia., bears N.22½°E., 20 lks, mkd CS 1/16 S9 BT
A hemlock, 11" dia., bears N.14°W., 21 lks. mkd. CS 1/16 S9 BT.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 8/5/2024 - C.S. File 67/58-43

Found - 3¼" BLM brass cap (properly mkd) up 2"
Burned, dead 27" D.Fir N.28°E., 12.9 ft. (rec. N.22½°E., 20 lks) add 3½" mag nail right side center.

Burned, sawn 18"x2 ft hemlock stump N.14°W., 13.2 ft. (rec. 21 lks) visible scar in log pile, not good reference.

New - 5/8"x30" iron rod with DCSO plastic cap up 4" S.79°E., 16.8 ft. set in west edge of westerly road shoulder.

Note - Mon on steep WNW slope SW quad is clear cut, rest is burned, partly cleared forest.
Mon is 25 ft. west of gravel road.
Area burnt 9/2020
Compass decl. 14¼°E.

Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 176626.032 E 268198.464