

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4214)

Set post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on N face, from which

- A laurel, 4" dia., bears N.20°W., 15 lks., mkd: ¼ S BT.
- A laurel, 5" dia., bears S.51°E., 10 lks., mkd: ¼ S BT.

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12743)

Point for the ¼ sec. cor. of secs. 4 & 9, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked:

T26S R2W
¼ S 4
 S 9
 1959

from which

- A fir, 14" dia., bears N.45°W., 27 lks., mkd: ¼ S4 BT.
- A fir, 12" dia., bears S.5°W., 5 lks., mkd: ¼ S9 BT.

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #990, surveyed Aug/Sept 1979 - (DCSO records Vol. 44 Page(s) 16944)

The ¼ sec. cor., of secs. 4 & 9, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with rock collar, 2 ft. dia., with brass cap (properly) mkd., from which the bearing trees mkd. by Zirpel and Glenn

- A fir, 16" dia., bears S.5°W, 5 lks., with healed blaze.
- A fir stump, 19" dia., bears N.45°W., 27 lks. dia., with healed blaze.

and a new bearing tree

- A fir, 19" dia., bears N.89½°E., 89 lks., mkd. ¼ S4 BT.

Cor, is located on S. edge of logged area, edge bears E & W.

Ron Quimby - Crew: N. Fromdahl, L. Heddens & J. Ogden - 10/2020 - C.S. File 65/106-57

Found - 1959 BLM brass cap (properly marked)
32" burnt fir S.5°W., 3.3 ft. scar burnt out.
Burnt fir snag N.45°W., 17.8 ft. no scar remains
33" burnt fir N.89½°E., 58.9 ft. healed scar.

Continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New - 5/8"x30" I.Rods with yellow plastic cap stamped "ie
ENGINEERING" with post alongside:
N.36°E., 8.0' S.48°E., 6.5'
S.75°W., 5.6' N.34°W., 6.8'
Note - Compass decl. 15½°E.