

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs 27, 28, 33 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Wm. N. Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCS0 records Vol. 10 Pages 4231-2)

Set granite stone, 8x10x16" 11" in the ground for cor. secs. 27, 28, 33, & 34, marked with 1 notch on S & 3 notches on E edge, from which

- A fir, 10" dia. bears N.29°E. 26 lks. mkd: T26S R2W S27 BT
- A cedar, 20" dia., bears S.78°E., 20 lks., mkd: T26S R2W S34 BT.
- A fir, 5" dia. bears S.78°W., 27 lks. mkd: T26S R2W S33 BT
- A cedar, 18" dia., bears N.29°W., 23 lks., mkd: T26S R2W S28 BT.

GL0 resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCS0 records Vol. 10 Page(s) 4312)

Cor. of secs. 27, 28, 33, & 34, established by Deputy Gibb in 1909, which is a granite stone, 5x10x8" above ground, firmly set, marked & witnessed as described by the surveyor general, except that they NE BT is a hemlock instead of a fir, & the SW BT a cedar instead of a fir, as described.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - March 1967 - C.S. File 54/40-15

Found - No trace of corner stone.

- Orig. 10" now 22" hemlock (record called for Fir, N.29°E.) N.25°E., 17.2 ft., alive, scribe visible on previously opened blaze.
- Orig. 20", now 25" cedar S.78°E., 13.2 ft. alive, shows scribe on previously opened blaze.
- Orig. 5" now 7" cedar, down (called for Fir) S.78°W., 17.8 ft. open & find scribe & reverse.
- Orig. 18" cedar, now down, N.29°W., 15.2 ft. shows scribe on unhealed blaze.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T26S R2W
OFFICE S 28 | S 27
1967 S 33 | S 34

New BTs- 10" hemlock N.67°W., 10.0 ft mkd: T26S R2W S28 CS BT
9" hemlock S.46°W., 7.7 ft. mkd: T26S R2W S33 CS BT
Orig. 25" cedar S.78°E., 13.2 ft. rescribed T26S R2W S34 CS BT.
Orig. 22" hemlock N.25°E., 17.2 ft. rescribed T26S R2W S27 CS BT.

continued next page

PRIMARY CORNER DESCRIPTION Cor Secs 27, 28, 33 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #990, surveyed Aug/Sept 1979 - (DCSO records Vol. 44 Page(s) 16941-2)

The cor. of secs. 27, 28, 33 & 34, perpetuated & recorded by Tracy, in 1967, monumented with an iron pipe, 1¼" dia., firmly set, projecting 4" above mound of stone, 3 ft. base, 1½ ft. high, with brass cap (properly) mkd., from which the remains of the original BTs remarked by Tracy

A hemlock stump, 27" dia., bears N.34°E., 26 lks., with illegible scribe marks visible on partially healed original blaze, and scribe marks R2W S27 CS BT visible on open blaze. (Record, N.29°E.)

A cedar stump, 25" dia., bears S.78°E., 20 lks., with illegible scribe marks visible on opened original blaze, and scribe marks T26S R2W S34 CS BT visible on open blaze.

and bearing trees mkd. by Tracy

A hemlock, 10" dia., bears S.43°W., 12 lks. with illegible scribe marks visible on partially healed blaze.

A hemlock, 10" dia., bears N.67°W., 15 lks. with illegible scribe marks visible on partially healed blaze.

No other suitable bearing trees available.
Cor. is located on W. edge of logged area, edge bears N. & S.

Fd. Ok 6/1983 by R. Geisler, M94-80
Fd. ok 7/1999 by D. Edwards C.S. 65/25-4

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2331, Surveyed April/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22929)

The cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 1¼" dia., firmly set, projecting 10" above a collar of stone, with brass cap (properly) mkd. from which the remains of the original bearing trees

A sawed, decayed, hemlock stump, 25" dia., bears N.34°E., 17.2 ft., with fragmentary scribe marks visible on partially healed original blaze and scribe marks 26S R27 CS BT visible on an additional partially healed blaze.

A sawed cedar stump, 26" dia., bears S.78°E., 13.2 ft., with fragmentary scribe marks visible on a partially healed blaze and scribe marks T26S R34 CS BT visible on an additional partially healed blaze.

and the remains of the BTs mkd. by the Douglas County Surveyor's Office in 1967

continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A hemlock, 16" dia., bears S.43°W., 7.9 ft., with a healed double blaze.
A hemlock, 13" dia., bears N.67°W., 9.9 ft., with a healed double blaze.
and new bearing trees
A cedar, 7" dia., bears N.31¼°E., 42.2 ft., mkd. T26S R2W S27 BT.
A fir, 5" dia., bears S.65°E., 19.8 ft., mkd. X BT.
Corner is located in a shallow draw, drains N.10°W.