

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. N. Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Pg 4233)  
-----  
Set granite stone, 10x10x16", 11" in the ground for ¼ sec. cor. mkd: ¼ on W face from which  
    A hemlock, 12" dia., bears N.60°W., 14 lks. mkd: ¼ S28 BT.  
    A hemlock, 8" dia., bears N.36°E., 28 lks., mkd: ¼ S27 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4329)  
-----  
Intersect the ¼ sec. cor. established by Deputy Gibb in 1909, which is a granite stone, 5x10x10" above ground, firmly set, marked & witnessed as described by the surveyor general.

Ronald G. Geisler, LS 1988 - For: Champion International Corp. - June - Aug. 1983 - M94-80  
-----  
Set - 2½" alum. cap on a 7/8" x 36" I.P. properly marked and stamped "PLS 1988" at the exact position of the orig. 1909 stone, 5"x15"x10" found. No markings on stone, which was partially buried alongside the I.P  
Found - Orig. BT, 21" hemlock bears N.60°W., 9.2 ft. scribed ¼ S28 BT.  
New BT- 9" hemlock bears N.56°E., 35.3 ft. scribed ¼ S27 BT.