

PRIMARY CORNER DESCRIPTION C C Secs. 21 & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. N. Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO rec Vol. 10 Pages 4233-4)

-----

Set a granite stone 6x8x14", 10" in the ground for cor. for cor. of secs. 21, 22, 27, & 28 marked with 3 notches on E & 2 notches on S edges, from which

- A laurel, 10" dia., bears N.49°E., 39 lks., mkd: T26S R2W S22 BT.
- A cedar, 30" dia., bears S.15°E., 43 lks., mkd: T26S R2W S27 BT.
- A maple, 7" dia., bears S.12°W., 75 lks., mkd: T26S R2W S28 BT.
- A laurel, 8" dia., bears N.18°W., 33 lks., mkd: T26S R2W S21 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4330-1)

-----

30.39 ch Intersect the closing cor. of secs. 21 & 28, established by me in 1916, which is an iron post, 3 ft. long, 2" dia, 12" above ground, marked & witnessed as described by the surveyor general. I now destroy this cor.

32.48 ch Intersect new W bdy of sec. 22

At the point of intersection

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for closing cor. of secs. 21 & 28, with brass cap mkd:

	T26S	T26S
	S 21	R2W
CC	S 28	S 22
	R2W	
	1918	

from which

- A hemlock, 6" dia., bears S.32°W., 33 lks., mkd: C C T26S R2W S28 BT.
- A fir, 40" dia., bears N.11°W., 50 lks., mkd: C C T26S R2W S21 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - Aug 1967 - C.S. File 54/40-59

-----

Found - GLO brass cap, properly marked in 1918

- 6" now 12" hemlock, snag, S.32°W., 21.8 ft. opened & fd scribing "8"
- 40" now 46" fir N.11°W., 33.0 ft. shows good face.

New BTs- 10" hemlock N.79½°W., 18.1 ft. mkd. T26S R2W S18 CC CS BT.

continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION C C Secs. 21 & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

12" hemlock S.45°W., 13.0 ft. mkd. T26S R2W S28 CC  
CS BT.  
Note - This corner lies 360 ft. south of logging road.

FD. Ok by D. Edwards 2/2004 - M143-66  
Fd. Ok by T. Hostetter, 12/2005 - M149-17

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff  
Lorsung- 5/11/2023 - C.S. File 67/56-17  
-----  
Found - 1918 GLO brass cap (properly mkd) up 14" in rough  
mound of stone.  
Burned remnant of Hemlock at root hole N.79¼°W.,  
18.1 ft.  
Area steep and burnt.  
New - 5/8"x30" I.rod N.46°E., 7.2 ft., up 4".  
5/8"x30" I.rod S.50°E., 7.2 ft., up 4".  
Note - Corner is approx. 300' south of logging road.  
Area burnt 9/2020  
Compass decl. 14½°E.  
Oregon Coordinate Reference System  
Cottage Grove - Canyonville Zone  
N 165244.149  
E 270686.079