

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec 22 only, West

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Page(s) 4236)

-----

Note - The decision was made not to type Wm. Gibb's corner information, due to the fact that when Fred Mensch executed his resurvey in 1918, the corner was moved by 27.63 chs. DCSO - JC

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4326)

-----

Set an iron post, 3 ft. long, 1" dia., 25" in the ground, for 1/4 cor. of sec. 22 only, with brass cap mkd. 1/4  
| S22  
1918

from which

A fir, 40" dia., bears N.79°E., 106 lks., mkd: 1/4 S22 BT.

A fir, 36" dia., bears S.85°E., 47 lks., mkd: 1/4 S22 BT.

Cor. established by Gibb as 1/4 on W bdy of sec. 22 bears S.15°47'E., 27.63 chs & 1/4 cor. on E bdy of sec. 21, established by said deputy, bears N.44°17'E., 10.69 chs.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - July 1967 - C.S. File 54/40-37

-----

Found - 1918 GLO brass cap mkd properly, set in mound of stone.

40" now 42" fir snag, N.79°E., 70.0 ft. shows good scar.

36" now 38" fir, alive, S.85°E., 31.0 ft. shows good scar.

New BTs- 9" W.Fir, N.52°E., 24.3 ft. mkd. 1/4 S22 CS BT

14" Cedar S.8°E., 13.8 ft. mkd. 1/4 S22 CS BT

Note - This corner lies approx 400 ft. S of old road from Smith's Ford Bridge on moderate N slope.

Douglas Co. Surveyors Office - Randall Smith - Stephen Flause - Oct. 20, 1994 - C.S. File 64/52-12

-----

Found - GLO 2 1/2" Brass cap on a 1" O.D. iron pipe protruding 11" above a 2' dia. mound of stone. (1918 GLO)

40" now 36" dia. 35' high D.Fir snag with a fully healed single blaze, bears N.79°E., 70.0 ft. (1918 GLO)

36" now 38" dia. D.Fir with a fully healed single blaze, bears S.85°E., 31.0 ft. (1918 GLO)

continued next pg

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 400333

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec 22 only, West

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

	9" now 13" dia. W.Fir with a fully healed double blaze, bears N.52°E., 24.3 ft. (1967)
	14" now 19" dia. R.Cedar with a fully healed single bears S.8°E., 13.8 ft. (1967)
New -	8" dia. Pine double blazed and scribed "¼ S22 CS BT" bears S.26°E., 25.7 ft.
Note -	Corner lies approximately 400 ft. south of a gravel Rd. on a moderate north slope.