

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 400346

PRIMARY CORNER DESCRIPTION SE Cor. Tract 37 (Cor. No. 7)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4339-40)

Intersect W bdy of sec. 22 & temp SE cor. of Tract 37. Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for cor. No. 7 of Tract 37, with brass cap mkd:

TR 37	T26S
7	R2W
S 21	S22
1918	

from which

A cedar, 6" dia., bears N.21°W., 76 lks. marked 7 TR 37 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - Aug. 1967 - C.S. File 54/40-6

Found - 1918 GLO brass cap properly mkd.
Orig. 6" now 18" cedar, alive, N.21°W., 50.2 ft., scribe visible on previously opened blaze.
New BTs- 10" D.Fir N.46°W., 20.9 ft. mkd. 7 Tr 37 CS BT.
22" Cedar N.46°E., 12.5 ft. mkd. 7 Tr 37 CS BT.
Note - This corner lies 10 ft. west of dry creek bed, 4 ft. wide, course N.

FD. Mensch BC, by G Lang, 11/2013 - C.S. file 65/79-17