

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor Secs 15, 16, 21, & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4205)

Note - The decision was made not to type John A. McQuinn's corner information, due to the fact that when subsequent re-surveys were performed some corners were changed substantially. DCSO - JC

GL0 survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Page(s) 4229)

Fd. stake, marked & witnessed as described by the Surveyor general.

GL0 resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4316, 4325 & 4340)

Page 4316
Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 15, 16, 21, & 22, with brass cap mkd:
NOTE ADDED: T26S R2W
SHOULD BE MARKED S 16 | S 15
TRACT 37 INSTEAD S 21 | S 22
OF S 21 1918
from which
A sugar pine, 20" dia., bears N.60°E., 31 lks., mkd: T26S R2W S15 BT.
A laurel, 16" dia., bears S.44°E., 16 lks., mkd: T26S R2W S22 BT.
A fir, 10" dia. bears S.76°W. 12 lks. mkd: T26S R2W S21 BT
NOTE ADDED: SHOULD BE MARKED TRACT 37 INSTEAD OF S 21
A Fir, 8" dia., bears N.74°W., 6 lks. mkd: T26S R2W S16 BT
Page 4325 The orig. McQuinn cor. of secs. 15, 16, 21, & 22, identified by Gibb & re-established by me in 1916 as cor. of secs. 15 & 16, bears S.56°17'E., 50.56 chs. I destroy marks on iron post & new BT.
Page 4340 Intersect cor of secs. 15, 16, 21, & 22. I now place additional marks on this post to designate it as cor. No. 8 of Tract 37. This post is now marked

8 TR 37 T26S R2W
 S 16 | S 15
 S 21 | S 22
 1918

continued next page

1

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor Secs 15, 16, 21, & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12729)

The cor. of secs. 15 & 22 only, which is also cor. No. 8 of Tract 37, monumented with an iron post, 2" dia., protruding 8" above ground, firmly set in a mound of stone, 3 ft. base, to top, set by Mensch in 1918 with brass cap (properly) mkd: from which 1918 BTs

A sugar pine, 32" dia., bears N.60°E., 31 lks., with a healed blaze.

A madrone, 18" dia. bears S.44°E., 16 lks., with scribe marks 2 22 B visible on a partially healed blaze.

A fir snag, 12" dia., bears S.76°W., 12 lks., with a healed blaze.

A fir, 10" dia., bears N.74°W., 6 lks., with a healed blaze.

add one new bearing tree

A fir, 10" dia., bears S.20¾°W., 31 lks., mkd: T26S R2W S21 BT.

FD. Mensch BC, by G Lang, 11/2013 - C.S. file 65/79-17

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24055)

The cor. of secs. 15 and 22 only, identical with cor. No. 8 of Tract 37, reported by Zirpel, Jr., and Glenn in 1959, monumented with an iron post, 2" dia., firmly set, projecting 3" above ground, in a collar of stone, with a brass cap (properly) mkd.

from which the remains of the bearing trees reported by Zirpel, Jr., and Glenn

A pine, 49" dia., bears N.60°E., 20.5 ft., with a healed blaze.

A madrone, 18" dia., bears S.44°E., 10.6 ft., no marks visible.

A fir, 14" dia., bears S.20¾°W., 20.5 ft., with a healed blaze.

A decayed fir stump, 12" dia., bears S.76°W., 7.9 ft., with a healed blaze.

A fir, 19" dia., bears N.74°W., 4.0 ft., with a healed blaze.

NAD 1983 (2011)

Latitude: 43°17'56.87" N. Longitude: 122°55'58.23" W.

continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor Secs 15, 16, 21, & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 1/19/2023 - C.S. File 67/55-26

Found - 1918 BLM brass cap flush in rough mound of stone.
48" S.Pine N.60°E., 20.5 ft. healed blaze.
Down, dead, 18" Madrone roothole bears S.44°E., 10.6
ft., fallen on face NW'ly.
19" D.Fir N.74°W., 4.0 ft., healed blaze.
14" D.Fir S.20¼°W., 20.5 ft., healed blaze, burnt
but still alive.

Note - Area burnt 9/2020
Add flagging and new BT tags.
Compass decl. 14½°E.

Lat: 43°17'56.35" N Long: 122°55'58.18" W