

PRIMARY CORNER DESCRIPTION NE Cor. Tract 37

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4336-7)

The NE Cor. of Tract 37, 13.23 chs. N.1°11'E., of cor. of secs. 15, 16, 21, & 22; at this point
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for cor. No. 1 of Tract No. 37, with brass cap mkd:

| | |
|-------|------|
| S 16 | T26S |
| 1 | R2W |
| TR 37 | S15 |
| 1918 | |

from which
A fir, 16" dia., bears S.74°W., 50 lks., mkd: 1 TR 37 BT.

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12730)

Cor. No. 1 of Tract 37, on the W bdy. of sec. 15, monumented with an iron post, 1" dia., firmly set, 8" above ground, and in a mound of stone, 3 ft. base, to top with brass cap (properly) mkd., from which the orig. BT
A sawed fir stump, 22" dia., bears S.74°W., 50 lks., with faint evidence of an old face.
add 2 new BTs
A fir, 12" dia., bears N.84°W., 34 lks., mkd: AP S16 BT.
A cedar, 6" dia., bears S.62°W., 61 lks., mkd: AP1 TR37 BT

BLM Dependent resurvey by Timothy J. Moore & Cadastral Surveyor & Robert H. Browning, Surveying Technician under Group #2000, surveyed July 2002 (DCSO rec. Vol. 54 pg(s) 21127-8)

Cor. No. 1, Tract 37, on the W. bdy. of sec. 15, monumented with an iron post, 1" dia., firmly set, projecting 8" above ground, in a mound of stone, 3 ft. base to top, with brass cap (properly) mkd.
from which the remains of an orig. bearing tree
A sawed and decayed fir stump, 25" dia., bears S.74°W., 33.0 ft., with scribe marks R 37 visible on open blaze.
and the remains of bearing trees mkd. by Zirpel and Glenn
A cedar, 14" dia., bears S.59¾°W., 40.3 ft., with a healed blaze. (Record, S.62°W.)
A decayed fir stump, size indeterminate, bears N.84°W., 22.4 ft., alongside of which is the fir trunk, 8" dia., with scribe marks AP S16 BT visible on open blaze.
and a new bearing tree continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 400413

PRIMARY CORNER DESCRIPTION NE Cor. Tract 37

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

A fir, 7" dia., bears N.35°W., 18.7 ft., mkd. AP S16 BT.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24055-6)

Corner No. 1 of Tract 37, on the W. bdy. of sec. 15, reported by Moore & Browning in 2002, monumented with an iron post, 1" dia., firmly set, projecting 16" above ground, in a mound of stone, 3 ft. base, 12" high, with a brass cap (properly) mkd from which the bearing trees reported by Moore

A cedar, 18" dia., bears S.59¼°W., 40.3 ft., with a healed blaze.

A decayed fir stump, 22" dia., bears S.74°W., 33.0 ft., with scribe marks TR 37 visible on open blaze. (Orig.)

A fir, 9" dia., bears N.35°W., 18.7 ft., with a healed blaze.