

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION W 1/4 Cor Secs 15 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Pg 4206)

Set post, 3 ft. long, & 3" sq., 24" in the ground for the 1/4 sec. cor. marked 1/4 S on W face, from which:
A laurel, 7" dia., bears N.20°E., 50 lks., mkd: 1/4 S BT.
A fir, 18" dia., bears S.80°W., 93 lks., mkd: 1/4 S BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4315)

Prior to permanent establishment of (other) corners
I make very exhaustive search for the 1/4 cor. of secs. 15 & 16

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12730-1)

Point for 1/4 sec. cor. of sec. 15 only, at midpoint on the W bdy of sec. 15.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap marked:
T26S R2W
| 1/4
| S 15
|
1959
from which
A fir, 22" dia., bears N.69 1/2°E., 33 lks., mkd: 1/4 S15 BT.
A fir, 11" dia., bears S.60 1/2°E., 36 1/2 lks., mkd: 1/4 S15 BT.
Corner falls on a small spur, slopes W.

Fd. Ok by K. DeGroot, 6/1999 - M131-58

David Edwards - For: Seneca Jones Tmbr - 1/2000 - M 134-15

Found BC & 2 BTs:
27" dia., fir brs. N.69 1/2°E., 21.78'
17" Fir brs. S.60 1/2°E., 24.09'
Per Narrative: The 1959 BLM resurvey set the 1/4 cor. And north 1/16 cor. On the west line of section 16 and called them for section 17 only. That same survey set the 1/4 cor. on the east line of sec 16 and called it for section 15 only. Analysis of the history of Sec 16, as well as an inquiry to the state office of the BLM, indicates that these corners should be common with section 16. Therefore I utilize said corners in computing the subdivision of section 16, as shown hereon.

Cont.

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION W 1/4 Cor Secs 15 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24056)

The ¼ sec cor of sec 15 only, reported by Zirpel, Jr. & Glenn in 1959, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with a brass cap (properly) mkd. from which the BTs reported by Zirpel, Jr., and Glenn

A fir, 31" dia., bears N.69½°E., 21.8 ft., with a healed blaze.

A fir, 20" dia., bears S.60½°E., 24.1 ft., with a healed blaze.