

PRIMARY CORNER DESCRIPTION N 1/16 Sec 15 only

Alias	Description

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12731)

Point for the N 1/16 sec. Cor. of sec. 15 only
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

| N 1/16
| S 15
1959

from which

- A Chinquapin, 21" dia., bears N.43½°E., 27 lks., mkd: N 1/16 S15 BT.
- A sugar pine, 8" dia., bears S.23¾°E., 96 lks., mkd: N 1/16 S15 BT.

BLM Dependent resurvey by Timothy J. Moore & Cadastral Surveyor & Robert H. Browning, Surveying Technician under Group #2000, surveyed July 2002 (DCSO rec. Vol. 54 pg(s) 21128)

The N 1/16 sec. cor. of sec. 15 only, monumented with an iron post, 2½" dia., firmly set, projecting 5" above ground, with brass cap (properly) mkd.
from which the remains of BTs mkd. by Zirpel and Glenn

- A chinquapin snag, 26" dia., bears N.43½°E., 17.8 ft., with fragmentary scribe marks visible on partially healed blaze.
- A pine, 29" dia., bears S.23¾°E., 63.4 ft., with no marks visible.

and a new bearing tree

- A fir, 8" dia., bears N.55½°E., 16.4 ft., mkd. N 1/16 S15 BT.

Kris DeGroot - For: James Wilkinson - 6/1999 (added 5/7/2024) - M131-58

Found - 2½" iron post by Zirpel & Glenn in 1959, firmly set, projecting 4" above the ground with a ¾" USBLM std. Brass cap (properly mkd) from which:

- A 27" Chinquapin bears N.42°45'E., 16.6 ft with a healed blaze (rec. N.43°30'E., 27 lks)
- A 30" Sugar pine bears S.23°45'E., 62.7 ft with a healed blaze (rec. 96 lks)

continued next page

1

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 400460

PRIMARY CORNER DESCRIPTION N 1/16 Sec 15 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24056-7)

The N 1/16 sec. cor. of sec. 15 only, reported by Moore and Browning in 2002, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd.

From which the BTs reported by Moore

A fir, 10" dia., bears N.55½°E., 16.4 ft., with a healed blaze.

A pine, 33" dia., bears S.23¾°E., 63.4 ft., with a healed blaze.

Corner is located E., 115 ft., of a graveled road, 12 ft. wide, bears N.10°E., and S.10°W., and N., 385 ft., of same graveled road, bears S.55°E. and N.50°W.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 4/29/2024 - C.S. File 67/57-54

Found - 3¾" USBLM brass cap (properly mkd) up 4"
Burned, dead 34" Sugar Pine S.23¾°E., 62.7 ft. fully healed single blaze, add 3½" mag nail right side center.

Burned, dead 10" Fir N.55½°E., 16.4 ft., fully healed double blaze, add 3½" mag nail right side center. 2002 BLM

Note - Area burnt 9/2020
Compass decl. 14½°E.
Mon is burned clear cut, burned forest in ~~SW~~ SE* quadrant. (Correction made by SJF 8/5/2024)
Mon is 60 ft east of gravel road on gentle westerly slope.

Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 173757.440 E 270711.165