

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4206)

Set a post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 9, 10, 15, & 16, marked T26S S10 on NE, R2W S15 on SE, S16 on SW, S9 on NW faces, with 4 notch on S & 3 notches on E edges; from which

- A laurel, 14" dia., bears N.10°E., 43 lks., mkd: T26S R2W S10 BT.
- A fir, 14" dia. bears S.10°E. 45 lks. mkd: T26S R2W S15 BT
- A laurel, 10" dia., bears S.61°W., 50 lks., mkd: T26S R2W S16 BT.
- A fir, 24" dia. bears N.55°W., 72 lks. mkd: T26S R2W S9 BT

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4315)

I commence at the cor. of secs. 9, 10, 15 and 16, which I verify as the original McQuinn cor. The cor., a post, is not found and has evidently been destroyed by fire or decay. The NE and SW bearing trees are down and marks obliterated by decay. The SE and NW trees are in good condition and marked as described by the surveyor general. Record measurements from the four trees give a common point. The bearings from this point are approximately correct. At this point I perpetuate the cor. by setting an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 9, 10, 15 and 16, with brass cap marked

T26S	R2W
S 9	S 10
S 16	S 15
1918	

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12731)

The cor. of secs. 9, 10, 15, & 16, perpetuated by Mensch in 1918, monumented with an iron post, 2" dia., firmly set, protruding 8" above ground, with brass cap (properly) mkd., from which 1883 BTs

- A sawed fir stump, 28" dia., bears S.14°E., 46 lks., with a healed blaze. (Rec. bearing & dist. S.10°E., 45 lks.)
- A sawed fir stump, 44" dia., bears N.46½°W., 78 lks., bark scribed T26S R2W S9 BT. (Rec. bearing & dist., N.55°W., 72 lks.)

continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and 4 new BTs

A fir, 6" dia. bears N.27°E., 40 lks. mkd: T26S R2W S10 BT

A fir, 10" dia., bears S.68½°E., 34½ lks., mkd: T26S R2W S15 BT.

A W.Fir, 12" dia., bears S.36¾°W., 43 lks., mkd: T26S R2W S16 BT.

A fir, 7" dia. bears N.57¾°W. 69½ lks. mkd: T26S R2W S9 BT

Fd. Ok by K. DeGroot, 6/1999 - M131-58