

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4208)

Set post, 3 ft. long, & 3" sq., 24" in the ground for the ¼ sec. cor. marked ¼ S on W face, from which:
A fir, 8" dia., bears S.60°E., 17 lks., mkd: ¼ S BT.
A willow, 5" dia., bears N.70°W., 12 lks., mkd: ¼ S BT.

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12733-4)

Point for the ¼ sec. cor. of secs. 9 & 10, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 16" in the ground to bedrock, & in a mound of stone, 3 ft. base, to top, with brass cap marked:

T26S R2W
 ¼
 S 9|S 10
 1959

from which
A fir, 12" dia., bears S.48½°E., 7 lks., mkd: ¼ S10 BT.
A fir, 14" dia., bears N.25¼°W., 16 lks., mkd: ¼ S9 BT.

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #990, surveyed Aug/Sept 1979 - (DCSO records Vol. 44 Page(s) 16944)

The ¼ sec. cor. of secs. 9 & 10, monumented with an iron post, 2½" dia., firmly set, projecting 2" above a mound of stone, 4 ft. base, 1½ ft. high with brass cap (properly) mkd from which BTs mkd. by Zirpel & Glenn
A fir, 16" dia., bears S.48½°E., 7 lks. with healed blaze.
A fir, 16" dia., bears N.25¼°W., 16 lks. with healed blaze
Cor. is located on top of rock bluff, edge bears N & S.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24078)

The ¼ sec. cor. of secs. 9 & 10, reported by Rogers in 1979, monumented with an iron post, 2½" dia, firmly set, projecting 14" above ground, in a mound of stone, 3 ft. base, 12" high, with a brass cap (properly) mkd.
from which the bearing trees reported by Rogers
A fir, 19" dia., bears S.48½°E., 4.6 ft., with a healed blaze.
Continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 18" dia., bears N.25¼°W., 10.6 ft., with a healed blaze.
Corner is located at the top of a rock bluff, edge bears N and S.
NAD 1983 (2011)
Latitude: 43°19'16.01" N. Longitude: 122°55'55.82" W