

PRIMARY CORNER DESCRIPTION Cor Secs 3, 4, 9, & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4208)

Set a post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 3, 4, 9, & 10, marked T26S S3 on NE, R2W S10 on SE, S9 on SW, S4 on NW faces, with 5 notch on S & 3 notches on E edges; from which

A fir, 5" dia., bears N.65°E., 27 lks. mkd: T26S R2W S3 BT
A fir, 7" dia. bears S.40°E., 20 lks. mkd: T26S R2W S10 BT
A fir, 5" dia., bears S.70°W., 32 lks. mkd: T26S R2W S9 BT
A fir, 6" dia., bears N.25°W., 27 lks. mkd: T26S R2W S4 BT

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12734)

Point for the cor. of secs. 3, 4, 9, & 10, proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 26" in the ground, with brass cap marked:

T26S	R2W		
S	4	S	3
S	9	S	10
1959			

from which

A fir, 14" dia., bears N.10¼°E., 48½ lks., mkd: T26S R2W S3 BT.
A sugar pine, 19" dia., bears S.39¼°E., 26½ lks., mkd: T26S R2W S10 BT.
A fir, 8" dia. bears S.37°W., 17½ lks. mkd: T26S R2W S9 BT
A fir, 23" dia. bears N.34°W., 27 lks. mkd: T26S R2W S4 BT

Ron Quimby - Crew: N. Fromdahl, L. Heddens & J. Ogden - 10/2020 - C.S. File 65/106-59

Found - 1959 BLM brass cap (properly marked)
Burnt 25" fir N.10°E., 32.0' healed scar
Burnt 13" Fir S.37°W., 11.5' healed scar.

New - 5/8"x30" I.Rods with yellow plastic cap stamped "ie ENGINEERING" with post alongside:
N.59°E., 8.5' S.26°E., 11.9'
S.39°W., 4.0' N.49°W., 7.75'

Note - Compass decl. 15½°E.