

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4 only, (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 9 Page(s) 3581)

-----

Set Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 3, 4, 33 and 34, mkd. T25S S34 on NE.; R2W S3 on SE.; T26S S4 on SW.; and S33 on NW. faces, with 3 notches on E. and W. edges. Raised mound of stone 2 ft. high, 4½ ft. base around post. No live trees near.

---

GLO survey by C.M. Collier, Deputy Surveyor, under Instructions dated May/Sept. 1913 - (DCSO records Vol. 10 Page(s) 4270 and 4274)

-----

(Page 4270)  
 Search for cor. of secs. 3 and 4, but find no trace of the markings. Set temp. cor. for sec. 3 and 4.

(Page 4274)  
 Set a Fir post 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 3 and 4, marked T26S S3 on SE.; and R2W S4 on SW. faces, with 3 notches on E. and W. edges; from which

- A Fir 18" dia., bears S.12°E., 5.12 chs. dist. mkd. T26S R2W S3 BT.
- A Fir 10" dia., bears S.22°W., 399 lks. dist. mkd. T26S R2W S4 BT.

(Notes of original cor. here are probably in error when the call for mound of stone, as there are no stones on this plateau.

---

BLM Resurvey by Irving Zirpel & Wm. Glenn Under Group #404, Surveyed May/Oct. 1959 - (DCSO records Vol. 30 Page(s) 12720)

-----

The cor. of secs. 3 and 4 only, perpetuated with an unmarked basalt stone, 14x10x8 ins., firmly set, at record distance from each of the bearing trees mkd. by Collier in 1913:

- A Fir 40" dia., bears S.16 3/4°E., 512 lks. dist. with scribe marks S3 B visible on an opened blaze. (Rec. brg. S.12°E.)
- A down and rotted Fir 14" dia., bears S.23¼°W., 399 lks. dist., with scribe marks BT and other illegible marks visible on opened blaze. (Rec. brg. S.22°W.)

At the corner point  
 Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:

T 25	S R 2 W
	S 34
	S 4   S 3
T 26	S R 2 W

(Cont. Next Page) 1959

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4 only, (North)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

from which  
A Fir 14" dia., bears S.14¼°W., 53½ lks. dist. mkd. T26S R2W S4 BT.  
Deposit the basalt stone alongside the iron post.

Fd. and used in BLM Resurvey by Daniel Berry; Harvey Wofford; G. Steven Popken, Cadastral Surveyors, under Group #'s 786, 848 and 854. And Glenn S. Baughman, L.S. #536, under Contract #52500-CT5-1116, Surveyed July 1972/Oct. 1975 - (DCSO records Vol. 36 Page(s) 15102-03)

Survey by Ronald Geisler - For: Champion International - June 30, 1987 - C.S. File 63/60-3

-----  
Found - 1959 BLM 3½" brass cap on a 2½" iron pipe, extends 4" above ground. Also found basalt stone alongside monument.  
24" D.Fir stump bears S.14¼°W., 35.3 ft. Face cut off. (1959 BT)  
New BT - 15" D.Fir bears S.55°E., 13.2 ft. scribed T26S R2W S3 CC BT.

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor and Robert H. Browning, Survey Technician, under Group #1754, surveyed May 1995 - July 1998 - (DCSO records Vol. 53 Page(s) 20453)

-----  
The cor. of secs. 3 and 4 only, T. 26 S., R. 2 W., monumented with an iron post, 2½" diam., firmly set, projecting 5" above ground, with brass cap mkd. T 25 S R 2 W  
S 34  
S 4 | S 3  
T 26 S R 2 W  
1959

from which the remains of an original bearing tree  
A fir, 49" diam., bears S.16 3/4°E., 512 lks., with no mks. visible on opened blaze.  
and the remains of a bearing tree mkd. by Zirpel and Glenn  
A sawed fir stump, 25" diam., bears S.14¼°W., 53½ lks., with no mks. visible.  
and a bearing tree mkd. by Geisler, in 1987  
A fir, 18" diam., bears S.57½°E., 20 lks., with fragmentary scribe mks. visible on partially healed double blazes.  
and a new bearing tree  
A fir, 3" diam., bears S. 27° W., 235 lks., mkd. X BT

continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4 only, (North)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Mark Smalley - For: Roseburg Resources - June 2003 - C.S.  
File 65/48-8

-----  
Found - BLM steel pipe & brass cap (properly mkd) & stone.  
50" Fir S.16 $\frac{3}{4}$ °E. 337.9' chopped out - rotting (Orig)  
20" Fir S.23 $\frac{3}{4}$ °W., 263.3' gone (no stump)  
24" rotten Fir stump S.14 $\frac{1}{4}$ °W., 35.3'  
19" Fir S.55°E., 13.2', scribe visible.  
New - 25" Fir S.16°E., 39.7' scribed "S3 BT"  
13" Fir N.2°W., 9.6' scribed "CC BT"

Ron Quimby - Crew: N. Fromdahl, L. Heddens & J. Ogden -  
10/2020 - C.S. File 65/106-61

-----  
Found - 1959 BLM brass cap  
24" burnt stump S.14 $\frac{1}{4}$ °W., 35.3'  
20" burnt snag S.55°E., 13.2' burnt scar  
25" burnt down fir S.16°E., 39.7' healed scar.  
14" burnt snag N.2°W., 9.6' burnt scar.  
New - 5/8"x30" I.Rods with yellow plastic cap stamped "ie  
ENGINEERING" with post alongside:  
N.34°E., 6.9' S.76°E., 7.9'  
S.30°W., 5.7' N.23°W., 5.0'  
Note - Compass decl. 15 $\frac{1}{2}$ °E.  
Area badly burnt 9/2020

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff  
Lorsung- 2/3/2022 (Filed 4/14/2022) - C.S. File 67/52-16

-----  
Found - 1959 BLM brass cap, proj. 4"  
24"x1 ft burnt stump S.14°W., 35.3 ft.  
15"x10' broken burnt snag S.57 $\frac{1}{2}$ °E., 13.0 ft. (rec.  
S.55°E., 31.2 ft) PK nail right side center.  
11"x6' burnt Fir snag N.2°W., 9.6 ft. PK nail right  
side center.  
4 - 5/8"x30" iron rods with yellow plastic cap  
stamped: ie ENGINEERING - N.34°E., 6.9 ft;  
S.76°E., 7.9 ft; S.30°W., 5.7 ft; and N.23°W.,  
5.0 ft. All with post along side.  
15" burnt & dead D.Fir S.27°W., 155.0 ft. to PK  
right side center. No blaze, no record, has BT  
tag with bearing to corner.  
Note - Area badly burnt 9/2020  
Compass decl. 14 $\frac{1}{2}$ °E.  
See sketch in file  
Lat: 43°20'37.62 N Long: 122°55'53.78" W