

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 420500

PRIMARY CORNER DESCRIPTION W 1/16 Secs 10 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Kris DeGroot - For: James Wilkinson - 6/1999 (added 5/7/2024)
- M131-58

Set - 5/8"x30" iron rod 28" in the ground with a aluminum cap
stamped: T26S R2W
 W $\frac{1}{16}$ $\frac{S10}{S15}$
 1999
 PLS 1941

from which new BTs:
 A 19" D.Fir bears S.82°E., 43.7 ft. scribed "W 1/16 S15
 BT"
 A 13" D.Fir bear N.29°W., 14.3 ft. scribed "W 1/16 S10
 BT"

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff
Lorsung- 4/29/2024 - C.S. File 67/57-53

Found - 2" alum cap (properly mkd) on 5/8" iron rod.
Burnt-sawn 26"x2' D.Fir stump S.85°E., 43.4 ft.
 (rec. S.82°E., 43.7') remains of healed blaze,
 add 3½" mag nail top center.
Burnt-sawn 24"x1½' D.Fir stump N.31°W., 13.9 ft.
 (rec. N.29°W., 14.3') remains of healed blaze,
 add 3½" mag nail top center.

Note - Mon on moderately steep SE slope ≈ 90' south of
 gravel road.
 Area burnt 9/2020
 Compass decl. 14½°E.
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 175365.9351 E 272054.0584