

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 431300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 22 only, South

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Page 4235)  
-----  
Set cedar stake, 3 ft. long, 4" sq. 24" in the ground for 1/4 sec. cor., mkd. 1/4 S 22 on N face & dig pits, 18x18x12", E & W of cor. & raise mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, N of cor., from which  
A chinquapin, 7" dia. bears N.22°E., 12 lks. mkd: 1/4 S22 BT

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4328)  
-----  
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 cor. of sec. 22 only, with brass cap mkd: 1/4 S22  
1918  
from which  
A cedar, 36" dia., bears N.15°E., 40 lks., mkd: 1/4 S22 BT.  
A fir, 8" dia., bears N.31°W., 24 lks., mkd: 1/4 S22 BT.  
Cor. established by Gibb as 1/4 cor. on N bdy. of sec. 27, bears N.0°51'E., 6.04 chs. & cor. established as 1/4 cor. on S bdy. of sec. 22 bears N.58°02'E., 11.41 chs.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - Aug. 1967 - C.S. File 54/40-53  
-----  
Found - 1918 GLO brass cap, firmly set, & properly marked. Orig. 8" now 14" Fir, turned out, N.31°W., 15.8 ft., prev. opened & shows scribe.  
No trace of NE BT  
New BTs- 9" hemlock, N.29°W., 21.7 ft. mkd. 1/4 S22 CS BT.  
15" cedar N.87°E., 44.9 ft. mkd. 1/4 S22 CS BT.  
Note - This corner lies on NE slope approx. 125 ft. W of old log access Rd.

Fd. Ok Feb. 2004, D. Edwards, M143-66

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 11/2/2021 (Filed 11/23/2021) - C.S. File 67/51-24  
-----  
Found - 1918 GLO brass cap.  
Root hole N.31°W., 15.8 ft.  
16"x2' sawn Hemlock stump N.29°W., 24.7 ft. 1967  
39"x2' R.Cedar sawn stump N.87°E., 44.9 ft., healed blaze. 1967  
New - 16"x2' sawn Hemlock stump N.29°W., 21.7 ft. 4" MAG NAIL top center.  
Continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 431300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 22 only, South

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

39"x2' R.Cedar sawn stump N.87°W., 44.9 ft. 8" MAG Nail top center.  
9"x7 ft. R.Cedar snag S.11°E., 26.1 ft. scribed "¼ S22 CS BT" on double blaze burnt.  
28"x4' sawn Fir stump N.86°w., 15.0 ft. 4" MAG NAIL top center.  
Steel marker post 2.0 North & 1.5 ft. South.  
Note - Corner is approx 125 West of old log Rd  
Area burnt in Archie Creek file 9/2020  
Compass decl. 15°E.  
See sketch in file.  
Lat: 43°17'05.38" N Long: 122°55'23.62" W