

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 436700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 34 only, T25-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by G. Robert Lecklider - For: Evans Products Co. -
Aug. 1960 - M 19-40

Set steel tube with survey cap, from which
40" Fir, N.86°E., 114.3 ft.
8" Fir, N.53°W., 33.0 ft.

BLM Resurvey by Daniel Berry; Harvey Wofford; G. Steven
Popken, Cadastral Surveyors, under Group #'s 786, 848 and
854. And Glenn S. Baughman, L.S. #536, under Contract #52500-
CT5-1116, Surveyed July 1972/Oct. 1975 - (DCSO records Vol.
36 Page(s) 15102)

Point for the ¼ sec. cor., at proportionate distance; there
is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 14" in the ground,
and in a mound of stone, 3 ft. base, to top, with brass cap
mkd:

T 25 S R 2 W
1/4 S 34
T 26 S R 2 W
1974

from which

A Fir 7" dia., bears N.61°E., 77 lks. dist. mkd. ¼ S34 BT.
A Fir 10" dia., bears N.16¼°W., 86½ lks. dist. mkd. ¼ S34
BT.

BLM dependent resurvey by Bryan S. Seibold, Cadastral
Surveyor and Robert H. Browning, Survey Technician, under
Group #1754, surveyed May 1995 - July 1998 - (DCSO records
Vol. 53 Page(s) 20451-2)

The 1/4 sec. cor. of sec. 34 only, reestablished by
proportionate measurement by Lecklider, in 1960, recorded in
the Douglas County Surveyors Office map file, M19-40, and is
accepted as the cor.; determined at recorded bearing and
distance from a bearing tree mkd. by Lecklider

A fir, 43" diam., bears N.86°E., 173 lks., with scribe
mks. 1/4 S34 RE4079 BT visible on a bark blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 25" in the
ground, with brass cap mkd.

T 25 S R 2 W
¼ S 34
T 26 S R 2 W
1998

from which bearing trees mkd. by Berry, Wofford, Popken and
Baughman continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 436700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 34 only, T25-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 12" diam., bears N.63½°E., 80 lks., with healed blaze.

A fir, 19" diam., bears N.14°W., 83 lks., with healed blaze.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, the point erroneously established as the 1/4 sec. cor. of sec. 34 only, by Berry, Wofford, Popken and Baughman in 1972-75, bears S.66°42'46"E., 0.050 chs. The 1972-75 survey failed to recover and accept Lecklider's corner. Monumented with an iron post, 2½" diam., firmly set, projecting 6" above a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. T25S R2W 1/4 S34 T26S R2W 1974, from which bearing trees mkd. by Berry, Wofford, Popken and Baughman

A fir, 13" diam., bears N.61°E., 77 lks., with healed double blazes.

A fir, 17" diam., bears N.16¼°W., 86½ lks., with healed double blazes.

The mks. on the brass cap were filed off and the brass cap was remarked AM 3.28 FT. TO COR. 1998 and an arrow pointing to the cor.