

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 34; & 3, T27-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by S.C. Flint, Contract #459, dated August 3, 1882
- (DCSO records Vol. 10 Page(s) 4183-84)

Set Laurel post 3 ft. long, 3" sq., 24" in the ground for ¼
sec. cor. marked ¼ S on N. and S. faces, from which
A Fir 20" dia., bears S.10°W., 30 lks. dist. mkd. ¼ S BT.
A Fir 18" dia., bears N.10°W., 15 lks. dist. mkd. ¼ S BT.

GL0 survey by C.M. Collier, Deputy Surveyor, under
Instructions dated May/Sept. 1913 - (DCSO records Vol. 10
Page(s) 4261-62)

The ¼ sec. cor., located by reference to the bearing trees,
as described by the surveyor general; all other traces of the
cor. have disappeared. I re-establish this cor. in its
original position as follows:
Set a basalt stone 20x10x8 ins., 15" in the ground, for ¼
sec. cor. marked ¼ on N. face, witnessed by the original
bearing trees as follows:
A Fir 20" dia., bears S.10°W., 30 lks. dist. mkd. ¼ S BT.
A Fir 18" dia., bears N.10°W., 15 lks. dist. mkd. ¼ S BT.

BLM Resurvey by Harold D. Corbin, Cadastral Surveyor, under
Special Instructions dated June 21, 1957 - (DCSO records Vol.
29 Page(s) 12204-05)

The ¼ sec. cor., monumented with a basalt stone 20x10x8 ins.,
10" above ground, firmly set, mkd. ¼ on the N. face, from
which the remains of the original bearing trees as follows:
A Fir 42" dia., bears N.10°W., 15 lks. dist. with a healed
blaze facing the cor.
A Fir 38" dia., bears S.10°W., 30 lks. dist. with a healed
blaze facing the cor.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 26" in the ground,
with brass cap mkd:

T26S R2W
¼ $\frac{S\ 34}{S\ 3}$
T27S

from which
A Madrone 11" dia., bears N.49½°E., 66 lks. dist. mkd. ¼
S34 BT.
A Fir 50" dia., bears S.23½°W., 77 lks. dist. mkd. ¼ S3 BT

Fd. Cor. and used in BLM resurvey by Wayne L. Rogers,
Cadastral Surveyor, Group #990, surveyed Aug/Sept. 1979 -
(DCSO records Vol. 44 Page(s) 16938)

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 34; & 3, T27-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. Ok by B. Shaner - 11/2000 - C. S. File 65/36-2F & M132-70

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 10/21/2025 - C.S. File 67/61-34

Found - BLM brass cap.
35" x 2 ft. fir stump N.10°W. 9.9 ft. (Rec 15 lks)
Burnt 27"x2 ft fir stump S.10°W. 19.8 ft (Rec 30 lks)
36" Madrone N.49½°E. 43.7 ft. (Rec 66 lks)
44" x 3 ft. fir stump S.23½°W. 50.8 ft. (Rec 77 lks)
All stumps have 3½" mag nails set top center.
T26S R2W
S34
S3
T27S

Notes - Mon on steep slope, logged and burnt to west.
Area burnt 9/2020
Compass decl. 14¼°E.
OCCRS COORDINATE SYSTEM
COTTAGE GROVE-CANYONVILLE ZONE
N. 154913.928 E. 273653.948