

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4207)  
-----  
Set post, 3 ft. long, & 3" sq., 24" in the ground for the ¼ sec. cor. marked ¼ S on N face, from which:  
A fir, 24" dia., bears N.35°E., 20 lks., mkd: ¼ S BT.  
A fir, 36" dia., bears S.5°E., 33 lks., mkd: ¼ S BT.

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12732)  
-----  
Point for the ¼ sec. cor. of secs. 10 & 15, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 26" in the ground with brass cap marked:  
T26S R2W  
¼  $\frac{S 10}{S 15}$   
1959  
from which  
A fir, 40" dia., bears N.27¼°W., 44½ lks., mkd: ¼ S10 BT.  
A fir, 16" dia., bears S.65¼°E., 137 lks., mkd: ¼ S15 BT.

FD. Ok by K. DeGroot, 6/1999 - M131-58

David Edwards - For: Roseburg Resources - 8/2009 - M 159-66  
-----  
Found - BLM Brass cap.  
BLM BTs are stumps as per M131-58  
New BTs- 5" dia., Cedar bears N.32°E., 28.2'  
6" dia., cedar bears S.63°E., 8.8'  
Set - 6' steel post 2' north.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24075)  
-----  
The ¼ sec. cor. of secs. 10 & 15, reported by Zirpel, Jr., & Glenn in 1959; perpetuated by Edwards, in 2009; monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, in a collar of stone, with a brass cap (properly) mkd from which the remains of the bearing trees reported by Zirpel, Jr., and Glenn  
A decayed fir stump, 18" dia., bears S.67¼°E., 90.4 ft., no marks visible. (Record, S.65¼°E.)  
A decayed fir stump, 44" dia., bears N.27¼°W., 29.4 ft., with a healed blaze. Continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the bearing trees mkd. by Edwards  
A cedar, 7" dia., bears N.32½°E., 28.1 ft., with scribe marks ¼ S10 BT visible on partially healed blaze.  
A cedar, 10" dia., bears S.64¼°E., 8.8 ft., with scribe marks ¼ S15 BT visible on partially healed blaze.