

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 440540

PRIMARY CORNER DESCRIPTION C 1/4 Sec 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

G. R. Lecklider - For: Mrs. O.A. Messing - Dec. 1959 - M16-68

Set - Steel tube with survey cap
16" Fir N.7°W., 55.2 ft.
18" Fir S.35°E., 23.8 ft.

David Edwards - For: Roseburg Resources - 8/2009 - M 159-66

Found - Pipe with alum. cap per M16-68
30" fir bears S.35°E., 23.8'
18" fir bears N.7°W., 55.2'
Both with healed blaze.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24075-6)

The center ¼ sec. cor. of sec. 10, established by Lecklider, 1959; and is accepted as the cor.; monumented with an iron post, 5/8" dia., firmly set, projecting 3" above ground, in a collar of stone, with an aluminum
A fir, 33" dia., bears S.35¼°E., 23.4 ft., with a healed blaze.
A fir stump, 25" dia., bears N.6¼°W., 55.0 ft., with a healed blaze.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, directly over the iron rod, in a collar of stone, with brass cap mkd.
T 26 S R 2 W
C ¼ S 10
2018
from which a new bearing tree
A fir, 9" dia., bears N.34½°E., 26.9 ft., mkd. C¼ S10 BT. Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument unless a similar marker was already in place.