

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO rec Vol. 10 Pg 4209)  
-----  
Set post, 3 ft. long, & 3" sq., 24" in the ground for the ¼ sec. cor. marked ¼ S on N face, from which:  
A fir, 30" dia., bears N.17°E., 22 lks., mkd: ¼ S BT.  
A fir, 6" dia., bears S.20°E., 33 lks., mkd: ¼ S BT.

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12735)  
-----  
Point for the ¼ sec. cor. of secs. 3 & 10, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 26" in the ground with brass cap marked:  
T26S R2W  
¼ S 3  
S 10  
1959  
from which  
A fir, 10" dia., bears N.20°E., 36 lks., mkd: ¼ S3 BT.  
A fir, 18" dia., bears S.59¼°E., 42 lks., mkd: ¼ S10 BT.

Ken Hoffine, Lone Rock Timber Co. - Witness: Gary Angiolet & Adam DeGroot - 4/14/2015 - C.S. File 65/89-19  
-----  
Found - 1959 BLM cap as per page 12735  
23" D.Fir Bears S.59¼°E., 27.5 Ft. (Record S.59¼°E., 27.72 ft.) well healed face.  
New - 9" Hemlock Bears N.1¼°W., 21.35 ft. we scribe ¼ S3 BT and tag tree.  
Note - Corner lies approx. 30 ft. south of small draw, on northwest slope. We ran a closed loop random traverse starting at the Northwest section corner of section 10 and running to the N¼ of section 10 and back to the Northwest section corner. We then blazed, painted, and tagged true line between the Northwest section corner and the North ¼ of section 10.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24077)  
-----  
The ¼ sec cor of secs 3 & 10, reported by Zirpel, Jr, & Glenn in 1959; perpetuated by Hoffine, in 2015; monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd. Continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the BT reported by Zirpel, Jr., and Glenn  
A fir, 23" dia., bears S. 59 1/4° E., 27.7 ft., with a  
healed blaze.  
and a BT mkd. by Hoffine  
A hemlock, 9" dia., bears N.13/4°W., 21.4 ft., with scribe  
marks 1/4 S3 BT visible on partially healed blaze.  
Corner is located S., 30 ft., of a draw, drains N.60°W.