

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 3 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 9 Page(s) 3581)

Set Fir post 3 ft. long, 3" sq., 24" in ground for ¼ sec. cor. mkd. ¼ on N. face, from which
A Willow 4" dia., bears N.75°E., 10 lks. dist. mkd. ¼ S BT
A Willow 4" dia., bears S.40°W., 29 lks. dist. mkd. ¼ S BT

GL0 survey by C.M. Collier, Deputy Surveyor, under Instructions dated May/Sept. 1913 - (DCSO records Vol. 10 Page(s) 4270 and 4274)

(Page 4270)
Search for ¼ sec. cor., but find no trace of it. Set temp. ¼ sec. cor.
(Page 4274)
Set a basalt stone 16x10x8 ins., 10" in the ground, for ¼ sec. cor. on N. line of sec. 3, marked ¼ on S. face, from which
A Chinquapin 4" dia., bears S.9°E., 98 lks. dist. mkd. ¼ S3 BT.
A Fir 4" dia., bears S.9°30'W., 38 lks. dist. mkd. ¼ S3 BT.

Survey by G. Robert Lecklider - July 30, 1959 - C.S. File 51/35

Found a stone 16" x 10" x 8" marked "¼" on S. face. Both BTs referring to this corner are gone.
Set 3/4" Iron rod next to stone, from which
I scribed a 26" D.Fir which bears S.55°W., 78.8 ft.

BLM Resurvey by Irving Zirpel & Wm. Glenn Under Group #404, Surveyed May/Oct. 1959 - (DCSO records Vol. 30 Page(s) 12719-20)

The ¼ sec. cor. of sec. 3 only, monumented by Collier with a basalt stone 16x10x4 ins., firmly set, 10" in the ground, mkd. ¼ on S. face, alongside of which has been driven an alum. rod, 1/2" dia., protruding 12" above ground, from the cor. point a locally established bearing tree:
A Fir 25" dia., bears S.55°W., 120 lks. mkd. T26S R2W ¼ S3 BT on an unhealed blaze.

At the corner point
(Cont. Next Page)

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 3 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:

¼ S 3
T 26 S R 2 W
1959

from which a new bearing tree:

A Fir 34" dia., bears S.29°E., 220 lks. mkd. ¼ S3 BT.
Deposit the original corner stone and the alum. rod alongside the iron post.

Fd. and Used in BLM Resurvey by Daniel Berry; Harvey Wofford; G. Steven Popken, Cadastral Surveyors, under Group #'s 786, 848 and 854. And Glenn S. Baughman, L.S. #536, under Contract #52500-CT5-1116, Surveyed July 1972/Oct. 1975 - (DCSO records Vol. 36 Page(s) 15101-02)

Fd. & used on BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor and Robert H. Browning, Survey Technician, under Group #1754, surveyed May 1995 - July 1998 - (DCSO records Vol. 53 Page(s) 20451)

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 12/9/2021 (Filed 4/12/2022) - C.S. File 67/52-5

Found - BLM brass cap
3/4" I.Rod
16"x10"x4" stone.
A burnt dead 45" Fir S.55°W., 78.5 ft. (rec. 79.2)
to nail right side center healed blaze. 1959
58" burnt dead Fir S.29°E., 145.0 ft. (rec. 145.2
ft) nail Rt. side center. 1959
New - 18"x7' sawed burnt Fir stump N.49°W., 13.5 ft., nail
Rt side center not blazed or scribed.
27" burnt dead Fir S.7°W, 7.8 ft nail Rt side center
not blazed or scribed.
Note - Area burnt 9/2020
Compass decl. 14½°E.
See sketch in file
Lat: 43°20'37.59 N Long: 122°55'19.03" W