

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 460200

PRIMARY CORNER DESCRIPTION E 1/16 Secs 27 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T.E. Shrum, Jr. - For: Champion International Corp. - 2/1979
- M76-56

Set - 2½" alum. cap
15" W.R. Cedar N.37°E., 9.4 ft.
7" D.Fir S.37W., 55.9 ft.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2331, Surveyed April/Oct. 2011 - (DCS0 records Vol. 58 Page(s) 22928)

The E 1/16 sec. cor. of secs. 27 and 34, established by Shrum, in 1979, by proportionate measurement, and is accepted as the cor.; monumented with an iron post, 1" dia., firmly set, projecting 14" above ground, with brass cap mkd.
T 26 S R 2 W RE 4287
E 1/16 $\frac{S\ 27}{S\ 34}$
1978
from which the bearing trees mkd. by Shrum
A cedar, 27" dia., bears N.36½°E., 9.9 ft., with two healed double blazes.
A fir, 20" dia., bears S.39¼°W., 54.5 ft., with a healed blaze.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 8/13/2024 - C.S. File 67/58-49

Found - 2½" alum cap on 1" iron rod up 14". Add rough mound of stone around iron post.
28" I.Cedar burned base N.36½°E., 9.9 ft., healed double blaze, add 3½" mag nail, right side center.
Sawn, burnt 25"x6 ft. Fir stump S.39¼°W., 54.5 ft. healed blaze, add 3½" mag nail, right side center
New - Sawn, burnt 20"x2 ft hemlock stump, N.86½°E., 2.4 ft., 3½" mag nail to center.
Note - Area burnt 9/2020
Compass decl. 14¼°E.
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 159974.294 E 275120.357