

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 460460

PRIMARY CORNER DESCRIPTION NE 1/16 Sec 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12753)

Point for the NE 1/16 sec. cor. of sec. 15, at intersection with the E. and W. center line of the NE 1/4.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd. NE 1/16 S 15
1959

from which

- A cedar, 10" dia., bears N.15°E., 32 1/2 lks., mkd. NE 1/16 S15 BT.
- A hemlock, 22" dia., bears S.75 1/2°W., 34 lks., mkd. NE 1/16 S15 BT.

David Edwards - For: Roseburg Resources Co - 8/2009 - M159-66

Found - BLM brass cap.
17" Cedar bears N.15°E., 21.5'
36" Sugar Pine (Hemlock) bears S.75 1/2°W., 22.4'
Both with healed blaze.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flauser and Jeff Lorsung - 12/18/2024 - C.S. File 67/59-33

Found - 3 1/4" BLM brass cap on 2 1/2" I.D. iron pipe, proj. 10" 24"x1 ft, burned, sawn Cedar stump N.15°E., 23.0 ft. (rec. 21.5 ft) evidence of blaze inside stump, add 3 1/2" mag nail top center.
48"x2 ft. burned, sawn Sugar Pine stump S.73 1/2°W., 22.4 ft. (rec. 75 1/2°W) fully healed single blaze, add 3 1/2" mag nail top center.
Alum post 0.5 ft. North
Steel post 2.0 ft. East.

Note - Area burnt 9/2020
Compass decl. 14 1/2°E.
Mon on moderate SSW slope in large clearcut large bench area 50'± N.W. NW-SE power line overhead.
Mon 130± NW of Star Mtn. Rd.

OCS COORDINATE SYSTEM
COTTAGE GROVE-CANYONVILLE ZONE
N 173854.876 E 274698.762