

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 9 Page(s) 3605)

At point of intersection, I set a basalt stone 18x8x6 ins., 12" in the ground for closing cor. of secs. 34 and 35 mkd. CC with 2 notches on E. and 4 notches on W. edges and raised a mound of stone 2 ft. base, 1½ ft. high N. of cor. Pits impracticable.

GLO survey by C.M. Collier, Deputy Surveyor, under Instructions dated May/Sept. 1913 - (DCSO records Vol. 10 Page(s) 4270)

Search diligently for traces of closing cor. of secs. 34 and 35, but find none.

BLM Resurvey by Irving Zirpel & Wm. Glenn Under Group #404, Surveyed May/Oct. 1959 - (DCSO records Vol. 30 Page(s) 12719)

Find no evidence of the closing cor. of secs. 34 and 25, T25S R2W.

Survey by G. Robert Lecklider - For: Evans Products Co. - Aug. 1960 - M 19-40

Set record distance from the sec. cor. 2 & 3, T26S R2W.
Set steel tube with survey cap., from which
14" Fir, N.45°W., 9.7 ft.
30" x 40" x 54" boulder, N.12°E., 6.6 ft. mkd. with an "X C C BO" on South face.

BLM Resurvey by Daniel Berry; Harvey Wofford; G. Steven Popken, Cadastral Surveyors, under Group #'s 786, 848 and 854. And Glenn S. Baughman, L.S. #536, under Contract #52500-CT5-1116, Surveyed July 1972/Oct. 1975 - (DCSO records Vol. 36 Page(s) 15100-01)

The closing cor., established by Lecklider in 1960, monumented with an iron pipe, 36" long, 1/2" dia., firmly set, protruding 12" above ground from which a bearing tree and bearing object mkd. by Lecklider:

A Fir 15" dia., bears N.49¼°W., 13 lks. dist., with healed blaze.

A rock in place, 54x40x30 ins., bears N.12°E., 10 lks. dist. with marks C|C BO visible on S. face.

At the corner point
(Cont. Next Page)

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 477700

PRIMARY CORNER DESCRIPTION C C for Secs. 34 & 35 only, T25-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set an iron post, 28" long, 2 1/2" dia., 16" in the ground,
and in a mound of stone, 3 ft. base, to top, with brass cap
mkd: T 25 S R 2 W

C|C
S 34|S 35
S 3

T 26 S R 2 W
1974

from which a new bearing tree:

An Alder 18" dia., bears N.35°E., 76 lks. dist. mkd. T25S
R2W S35 CC BT.

Fd. & used on BLM dependent resurvey by Bryan S. Seibold,
Cadastral Surveyor and Robert H. Browning, Survey Technician,
under Group #1754, surveyed May 1995 - July 1998 - (DCSO
records Vol. 53 Page(s) 20449)

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor
Under Group No. 2317, Surveyed June 2010/June 2011 - DCSO
records Vol. 57 Page(s) 22787

The closing cor. of secs. 34 & 35, on the S. bdy. of the Tp.,
monumented with an iron post, 2 1/2" dia., firmly set,
projecting 12" above the ground, (alongside of which is an
iron pipe, 1/2" dia., firmly set, projecting 16" above the
ground, with aluminum cap mkd. PROPERTY CORNER), with brass
cap (properly) mkd.

from which accessories mkd. by Lecklider, in 1960

A rock in place, 4 1/2 x 3 1/2 x 2 1/2 ft., bears N.18°E., 5.9 ft.,
with marks CC + BO visible on S. face.

A fir, 15" dia., bears N.49 1/4°W., 8.6 ft., with a healed
double blaze.

and a BT mkd. by Wofford, Berry, Popken, and Baughman

An alder, 18" dia., bears N.34 1/4°E., 51.5 ft., with scribe
marks T25S R2W S35 CC BT visible on the bark.