

PRIMARY CORNER DESCRIPTION SW Cor. to Sec. 26 only

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Wm. Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol 10 Page 4224-5)

Set granite stone, 8x10x14", 10" in the ground for cor. secs. 26, 27, 34, & 35, marked with 2 notches on E & 1 notch on S edge; from which

- A cedar, 12" dia., bears N.82°E., 51 lks., mkd: T26S R2W S26 BT.
- A fir, 12" dia., bears S.33°E., 104 lks., mkd: T26S R2W S35 BT.
- A cedar, 6" dia., bears S.85°W., 37 lks., mkd: T26S R2W S34 BT.
- A cedar, 14" dia., bears N.31°W., 151 lks., mkd: T26S R2W S27 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4307)

At the point of intersection
Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for SW cor. of sec. 6, with brass cap marked:

T26S
R2W
S26

1916

from which

- A cedar, 20" dia., bears N.23°E., 37 lks., mkd: ¼ S26 BT.

The cor. established by Deputy Gibb in 1909 as the cor. of secs. 26, 27, 34 & 35, which is a granite stone, 4x10x8" above ground, firmly set, marked & witnessed as described by the surveyor general, bears N.23°53'E., 21.96 chs.
I destroy the cor. set in the rejected revision survey as the cor. of secs. 26, 27, 34, & 35 & marks on BTs.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - D. West - July 1967 - C.S. File 54/40-22

Found - 1916 GLO brass cap, properly marked.
20", now 28" Cedar N.23°E., 24.4 ft., alive, previously opened & scribe visible. Only one BT was mkd for corner.

New BT - 12" W.Fir N.70°E., 21.8 ft. mkd: T26S R2W S26 CS BT.
Note - This corner lies on steep, southerly slope.

PRIMARY CORNER DESCRIPTION SW Cor. to Sec. 26 only

Alias	Description

BLM dependent resurvey by Dale Bedell & Bryan Seibold Cadastral Surveyors & Robert H. Browning, Survey Technician, under Group No. 1638, surveyed July 1992/April 1995 - (DCSO records Vol. 51 (Pages 19749-50)

The SW. cor. of sec. 26 perpetuated by Tracy, in 1967, and utilized by Shrum, in 1979; monumented with an iron post, 1" dia., firmly set, projecting 12" above the ground, with brass cap (properly) mkd.
from which the original bearing tree
A cedar, 28" dia. bears N.23°E., 37 lks. with scribe marks T26 R2 S26 BT visible on a partially healed blaze.
and a bearing tree mkd. by Tracy
The northerly trunk of a double hemlock, 14" dia., bears N.70°E., 33 lks., with a healed blaze.
The corner is located on a steep SW. slope.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2331, Surveyed April/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22925)

The cor. of sec. 26 only, monumented with an iron post, 2" dia., firmly set, projecting 14 ins. above ground, with brass cap (properly) mkd.
from which an original bearing tree
A cedar, 30" dia., bears N.23°E., 24.4 ft., with scribe marks T2 R2 S26 BT visible on a partially healed blaze.
and a BT mkd. the Douglas County Surveyor's Office in 1967
The northerly trunk of a double hemlock, 15" dia., bears N.70°E., 21.8 ft., with a healed blaze.