

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 500219

PRIMARY CORNER DESCRIPTION CC Secs. 27 & 34 (SE Cor. Sec. 27)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4313-4)

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for closing cor. of secs. 27 & 34, with brass cap mkd:

T26S T26S
S 27 |
CC _____ | R2W
S 34 |
R2W | S26
1916

from which

A sugar pine, 14" dia., bears S.45°W., 28 lks., mkd: T26S R2W S34 BT.

A fir, 14" dia. bears N.72°W. 23 lks. mkd: T26S R2W S27 BT

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2331, Surveyed April/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22925)

The cor. of secs. 27 & 34 only, monumented with an iron post, 2" dia., firmly set, projecting 16" above ground, with a brass cap mkd. T26S R2W 1913

from which the remains of the original bearing trees

A sawed, decayed, sugar pine stump, 21" dia., bears S.45°W., 18.5 ft., with a healed blaze.

A fir, 35" dia., bears N.72°W., 15.2 ft., with a healed blaze.

At the corner point

Raise a mound of stone, 3 ft. base, to top, and add marks to the brass cap to read

T26S R2W
CC S 27 | S 26
S 34 |
2011
1913

and a new bearing tree

A cedar, 9" dia., bears S.66¼°W., 33.7 ft., mkd. T26S R2W S34 BT.

Corner is located 70 ft. south of a rock face, 20 ft. high; edge bears generally E. and W.

The point for the S 1/16 on the west line of sec. 26 bears: N.0°10'18"W., 135.54' ...