

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 500220

PRIMARY CORNER DESCRIPTION S 1/16 west line Sec 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2331, Surveyed April/Oct. 2011 - (DCS0 records Vol. 58 Page(s) 22926)

-----  
Point for the S 1/16 sec. cor. of sec. 26 only, on the line between the cor. of secs. 27 & 34 only and the ¼ sec. cor. of sec. 26 only, at proportionate distance latitudinally between the cor. of sec. 26 only and the ¼ sec. cor. of sec. 26 only. Cement a brass tablet, 3½" dia., with 2½" stem, in a drill hole, in a rock outcrop, (deposit a magnet in drill-hole beneath stem) with cap mkd.

    | S 1/16  
    | S 26  
    2011

from which

    A fir, 26" dia., bears N.14°E., 21.5 ft. mkd. S1/16 S26 BT

    A fir, 11" dia., bears S.50½°E., 25.1 ft., mkd. X BT.

Corner is located 3 ft. N. of the southerly edge (bottom) of a rock outcropping, 10 ft. high, edge bears N.70°E. and S.70°W.

The CC secs. 27 & 34 (SE S 27) bears S.0°10'18"E., 135.34 ft.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 8/13/2024 - C.S. File 67/58-50

-----  
Found - 3¼" brass tablet in rock out crop.  
27" burned-dead D.fir snag N.14°E., 21.8 ft. (rec 21.5 ft) partly healed single blaze, add 3½" mag nail right side center.

Burned-sawn 11"x3 ft. D.Fir stump S.50½°E., 25.1 ft. healed lower blaze, add 3½" mag nail, right side center.

Alum post 1/2 ft. Westerly.

Note - Area burnt 9/2020.

Compass decl. 14¼°E.

Oregon Coordinate Reference System

Cottage Grove - Canyonville Zone

N 160114.378            E 275836.392