

PRIMARY CORNER DESCRIPTION East 1/4 Cor. Sec. 27 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. N. Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO recs Vol. 10 Page 4228)

Set granite stone, 8x10x14", 10" in the ground for ¼ sec. cor. mkd ¼ on E face, & raised mound of stone, 2 ft. base, 1½ ft. high, East of cor., from which
 A fir, 6" dia., bears N.55°E., 27 lks., mkd: ¼ S26 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4309)

The cor. established by Deputy Gibb in 1909 as the ¼ sec. cor. on E bdy of sec. 27, which is a granite stone, 5x12x5" above ground, firmly set, marked & witnessed as described by the surveyor general, except that no mound of stone is found, bears N.21°47'E., 18.67 chs.

T.E. Shrum, Jr - For: Champion Int. - Sept. 15, 1981 - M89-28

Set - 2½" alum. cap on a 1"x36" IP (1981) ¼ Corner 27 only
 6" hemlock N.62°W. 10.4'
 10" Hemlock N.31°30'W. 20.0'

Ronald Geisler - For: Champion Int. - Crew: Lynn Sibley & Dean Turner - June 30, 1987 - C.S. File 63/60-4

Found - 2½" alum, cap on a 1" iron pipe extends 11" above ground. 1981
 6" hemlock, leaning badly bears N.62°W., 11.5 ft. (Rec. 10.4 ft.) scribing visible. (1981)
 12" Hemlock now down and uprooted bears N.30°30'W., 20.0 ft. to root hole. Scribing visible. (1981)
New BTs- 11" Hemlock bears N.87°W., 40.7 ft. Scribed "S27 ¼ BT"
 9" Hemlock bears S.70°30'W., 42.8 ft. Scribed "S27 ¼ BT".