

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 500309

PRIMARY CORNER DESCRIPTION East Sec cor Secs 22 & 27 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4198-9)

Set a post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 22, 23, 26, & 27, marked T26S S23 on NE, R2W S26 on SE, S27 on SW, S22 on NW faces, with 2 notches on S & E edges; from which

- A fir, 12" dia. bears N.45°E. 11 lks. mkd: T26S R2W S23 BT
- A hemlock, 18" dia., bears S.60°E., 55 lks., mkd: T26S R2W S26 BT.
- A cedar, 18" dia., bears S.30°W., 43 lks., mkd: T26S R2W S27 BT.
- A fir, 10" dia. bears N.20°W. 10 lks. mkd: T26S R2W S22 BT

GL0 survey by Wm. N. Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Pg 4234)

Intersect N & S line, 15.41 chs N.54'E., of cor. secs. 22, 23, 26 & 27.

Set granite stone, 8x10x20", 15" in the ground for closing cor. secs. 22 & 27 marked CC on W face, with 2 grooves on S & 4 grooves on N face, from which

- A maple, 14" dia., bears S.30°W., 35 lks., mkd: T26S R2W S27 BT.
- A fir, 40" dia. bears N.70°W. 48 lks. mkd: T26S R2W S22 BT

I destroy markings on old cor. referring to secs. 22.

GL0 resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4327)

Intersect W bdy. of sec. 23, 8.99 chs. N.1°12'E. of cor. sec. 22, 23, 26 & 27, which I change to refer to secs 23 & 26 only
At the point of intersection

Set an iron post, 3 ft. long, 2" dia., 24" in th ground, for closing cor, of secs. 22 & 27, with brass cap marked

T26S
S22 | S 23
S27 |
1918

from which -

- A hemlock, 12" dia., bears S.49°W., 54 lks. mkd C C T 26 S 2 R 2 W S 27 B T
- A fir, 40" dia., bears N.20°W., 16 lks. mkd: C C T 26 S R 2 W S 22 BT

continued next page

1

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 500309

PRIMARY CORNER DESCRIPTION East Sec cor Secs 22 & 27 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

FD & used on BLM dependent resurvey by G. Steven Popken, Cadastral Surveyor, Group No. 871, surveyed June/Sept. 1975 - (DCSO Vol. 46 Page(s) 15723)
Ronald G. Geisler, L.S. 1988 - For: Champion International Corp. - June thru Aug. 1983 - M94-80 ----- Set - 2½" alum. cap set on a 7/8"x36" I.P. properly marked and stamped "PLS 1988". New BTs- 6" cedar bears N.79°W., 36.4 ft. scribed "T26S R2W S22 CC BT" 6" fir, bears S.29°W., 22.3 ft. scribed "T26S R2W S27 CC BT" Found - A 5/8" iron rod that bears S.89°39'44"W., 2.40 ft. Orig. 44" fir stump, bears N.30°15'W., 11.2 ft. closed face. Orig., 14" rotten hemlock stump bears S.50°W., 37.2 ft. Scribed "26S R2W S27 CC BT."
Fd. Ok by D. Edwards, Feb. 2004 - M143-66
Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 11/2/2021 (Filed 11/232/2021) - C.S. File 67/51-23 ----- Found - 2" alum. cap on 7/8" iron pipe, 1983, proj. 3" 18"x2' R.Cedar stump bears N.79°W., 36.4 ft. 1983 14" D.Fir S.29°W., 22.3 ft. fully healed double blaze. 1983 5/8" iron rod not found. New - 14"x1½' R.Cedar burnt stump with 4" MAG NAIL top center bears S.47°W., 14.6 ft. 20"x1 ft. tall burnt stump with 8" galvanized spike top & center bears S.70½°E., 27.1 ft. Note - Corner is approx. 30' South of gravel Rd. Area burnt 9/2020 Compass decl. 14½°E. See sketch in file Lat: 43°17'05.02" N Long: 122°54'48.79" W