

PRIMARY CORNER DESCRIPTION West 1/4 Cor. Sec. 23 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn under contract #466, dated April 5, 1883 - (DCSO records Vol. 10 page(s) 4199)

 Set hemlock post, 4" sq. 4 ft. long, 24" in ground for ¼ sec. cor. marked ¼ S on W face, from which
 A hemlock, 10" dia., bears S.80°E., 12 lks., mkd: ¼ S BT.
 A maple, 12" dia., bears N.70°W., 14 lks., mkd: ¼ S BT.

GLO survey by Wm. N. Gibb under contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 10 page(s) 4228-9)

 I retrace N bet. secs. 22 & 23
 Falls 67 lks. W of ¼ sec. cor., which is a stake greatly decayed, marked & witnessed as described by the Surveyor General.
 Set granite stone, 6x10x15", 10" in the ground for ¼ sec. cor. marked ¼ on W face.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, Group 56 - (DCSO records Vol. 10 Page(s) 4304)

 Intersect the orig. ¼ sec. cor. established by Deputy McQuinn in 1883 & reestablished by Deputy Gibb in 1909, which is a granite stone, 5x10x6" above ground, firmly set, marked as described by the surveyor general & witnessed by the orig. BTs of McQuinn survey. The BT on the east is now a dead & broken stub. I now perpetuate this cor. as follows:
 Set an iron post, 3 ft. long, 1" dia., in the ground, 1 lk. W of cor. with brass cap marked

¼	Note: This ¼ sec. is
S 22 S 23	now intended to
1916	refer to sec. 23
	only

 from which
 A hemlock, 14" dia., bears S.15°E., 44 lks., mkd: ¼ S23 BT
 A maple, 18" dia., bears N.89°W., 11 lks., mkd: ¼ S22 BT.

BLM dependent resurvey by G. Steven Popken, Cadastral Surveyor, Group No. 871, surveyed June/Sept. 1975 - (DCSO Vol. 46 Page(s) 15723-4)

 The ¼ sec. cor. of sec. 23 only, monumented with an iron post, 1" dia., firmly set, projecting 12" above ground, alongside of which is the granite stone, 16x10x5" set by Gibb, in 1909, mkd. ¼ on W. face. The brass cap (properly) mkd. from which the remains of the orig. BTs
 A Maple, 21" dia. bears N.89°W., 11 lks. with healed blaze and a BT mkd. by Mensch continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION West 1/4 Cor. Sec. 23 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A hemlock, 18" dia., bears S.21°E., 44 lks., with healed blaze. (Rec. S.15°E.)

Fd. Ok by D. Edwards, 2/2004 - M143-66