TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4201)

Set ash post, 3 ft. long, & 3" sq., 24" in the ground for the ¼ sec. cor. marked ¼ S on W face, from which:
An ash, 8" dia., bears N.60°E., 43 lks., mkd: ¼ S BT.
An ash, 10" dia., bears S.70°W., 13 lks., mkd: ¼ S BT.

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12725-6)

Point for the ¼ sec. cor. of secs. 14 & 15, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 22" in the ground and in a mound of stone, 1½ ft. base to top, with brass cap marked:

T26S R2W
¼
S 15 | S 14
1959

from which
A fir, 8" dia., bears East, 50 lks., mkd: ¼ S14 BT
A fir, 10" dia., bears N.86°W., 80 lks., mkd: ¼ S15 BT.
From this point the NE cor. of an abandoned wood frame building, bears S.33°31'W., 85 lks., dimensions 13x12 ft., long-side bears South.
From the same point the NW cor. of an abandoned wood frame building, bears S.37°17'E., 109 lks., dimensions 14½x10½ ft. long-side bears East.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 1/23/2023 - C.S. File 67/55-32

Found - 3¼" BLM brass cap (properly mkd) up 9"
Burned-dead 15" D.Fir N.88°E., 34.8 ft. (rec. East 33.0 ft) right side center.
New - 5/8"x30" I.Rod with DCSO yellow plastic cap up 4" N.84°W., 60.8 ft.
5/8"x30" I.Rod with DCSO yellow plastic cap up 4" N.6°W., 62.1 ft.
Note - Area burnt 9/2020
Compass decl. 14½°E.
Monument is approx 75 ft. south of gravel driveway curving SW'ly
Lat: 43°18'23.49" N Long: 122°54'47.00" W