

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor Secs 10, 11, 14, & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4201)

-----

Set a post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 10, 11, 14, & 15, marked T26S S11 on NE, R2W S14 on SE, S15 on SW, S10 on NW faces, with 4 notches on S & 2 notches on E edges; from which

- A fir, 24" dia. bears N.65°E. 53 lks. mkd: T26S R2W S11 BT
- A fir, 30" dia. bears S.20°E. 110 lks mkd: T26S R2W S14 BT
- A fir, 24" dia. bears S.30°W. 53 lks. mkd: T26S R2W S15 BT
- A fir, 30" dia. bears N.50°W. 15 lks. mkd: T26S R2W S11 BT

Douglas Co. Surveyors Office - Ben B. Irving, Co. Surveyor - Witnesses: R.L. Irving & Carl Messing - Dec. 5, 1927 - C.S. File 14/31

-----

Location identified OBTs

- Fir 30" dia., N.62°10'E., 53 lks.
- Fir 30" S.22°40'E., 99 lks.
- Fir 30" S.25°20'W., 53 lks.
- Fir 36" N.40°25'W., 16 lks.

Set stone 4x6x16 4 notches S. cor. - 2 notches E cor. - "X" on top - in mound of rock 24" dia., 12" high.

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12726-7)

-----

The cor. of secs. 10, 11, 14, & 15, perpetuated & recorded by Irving, in 1945 (1927 per "Old Corner" book - DCSO), monumented with a basalt stone, 16x6x4", with an X on top, 4 notches on S & 2 notches on the E. edge, set in a mound of stone, 2 ft. base, 1 ft. high, from which the original BTs:

- A fir, 30" dia., bears N.63½°E., 53 lks., bark scribed by County Surveyor, T26S R2W S11 CS BT. (Record bearing N.65°E.)
- A sawed fir stump, 36" dia., bears S.22¾° E., 99 lks., no marks visible. (Record bearing & dist., S.20°E., 110 lks.)
- A sawed fir stump, 30" dia., bears S.27¼°W., 56 lks., bark scribed by County Surveyor S15 CS BT. (Record bearing & dist., S.30°W., 53 lks.)
- A fir, 36" dia. bears N.40¾°W., 16 lks. bark scribed by County Surveyor T26S R2W S10 CS BT. (Record bearing & dist., N.50°W., 15 lks.)

At the corner point

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor Secs 10, 11, 14, & 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Set an iron post, 28" long, 2½" dia., 14" in the ground, & in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 26 S R 2 W  
S 10 | S 11  
S 15 | S 14  
1959

Raise a mound of stone, 3 ft. base 2 ft. high West of the cor  
Deposit the basalt stone alongside the iron post.

Douglas Co. Surveyors Office - Milo Godfrey - Veron Tracy -  
Mike Stone - Oct. 1961 - C.S. File 52/77-9

-----  
Found - GLO Iron pipe & brass cap in mound of rock.  
36" D.Fir N.40½°W., 10.6 ft. good bark scribing visible (1927)  
30" Fir N.62°E., 35.0 ft., tree recently uprooted & down. Good bark scribing visible.  
30" Fir stump S.25½°W. 35.0 ft bark scribing visible  
30" Fir stump S.22½°E., 65.3 ft. bark gone from stump, no scars or scribing visible.  
New - 8" Madrone N.73°E., 48.7 ft. mkd: S11 CS BT.  
5" Maple S.86°E., 29.4 ft. mkd: S14 CS BT.  
5" D.Fir S.81°W., 121.4 ft. mkd: S15 CS BT.

Fd. Ok by R. Quimby 11/2001 - M139-15

Fd. & used on BLM dependent resurvey by Lynn M. Roseberry, Cadastral Surveyor, Group #664, surveyed April 1968 - (DCS0 records Vol. 34 Page(s) 14276-7)

BLM dependent resurvey by Dale T. Bedell & Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Survey Technician, under Group No. 1638, surveyed July 1992/April 1995 - (DCS0 records Vol. 51 (Page(s) 19750-1)

-----  
The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees  
A roothole, bears N.63½°E., 53 lks., with uprooted fir alongside, 30" dia., no marks visible.  
A sawed fir stump, 36" dia., bears S.22¾°E., 99 lks., no marks visible.  
A sawed fir stump, 30" dia., bears S.27¼°W., 56 lks., with fragmentary bark scribing visible.  
A fir, 36" dia., bears N.40¾°W., 16 lks., with scribe marks T26S R2W C BT visible.

continued next page

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

and the remains of BTs mkd. by Godfrey  
A madrone stump, 8" dia., bears N.72½°E., 74 lks., with reverse scribe marks BT visible. (Record, N.73°E.)  
A sawed maple stump, 5" dia., bears S.85¾°E., 45 lks., with decayed maple alongside, with scribe marks BT visible on opened blaze. (Record, S.86°E.)  
A fir, 12" dia., bears S.79¾°W., 184 lks., with healed double blaze. (Record, 184½ lks.)  
and new bearing trees  
A fir, 7" dia. bears N.55°E., 36 lks. mkd. T26S R2W S11 BT  
A fir, 10" dia. bears S.52°E. 47 lks. mkd. T26S R2W S14 BT  
From the sec corner, the BLM, Geodetic Control Station No. EC 41166, at latitude 43°18'50.0488"N longitude 122°54'39.1635"W (NAD 1927), determined by the NAVSTAR GPS, bears S.83°07'48"E., 2.883 chs. (mean bearing & sea level dist); monumented with an aluminum cap, ¾" dia., set in concrete in bedrock, with cap mkd. EC41166 GPS 1992 and a triangle.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24057)

-----

The cor. of secs. 10, 11, 14, & 15, reported by Bedell, Seibold, and Browning in 1992-95, monumented with an iron post, 2½" dia., firmly set, projecting 16" above ground, in a mound of stone, 2 ft. base, 12" high, with a brass cap (properly) mkd.  
from which the remains of the bearing trees reported by Bedell, Seibold, and Browning  
A fir, 12" dia., bears N.55°E., 23.8 ft., with a healed blaze.  
A madrone stump, 10" dia., bears N.72½°E., 48.8 ft., with no marks visible on open blaze.  
A decayed fir stump, 26" dia., bears S.22¾°E., 65.3 ft., no marks visible. (Original)  
A fir, 15" dia., bears S.52°E., 31.0 ft., with a healed blaze.  
A decayed fir stump, 30" dia., bears S.27¼° W., 37.0 ft., with a healed blaze. (Original)  
A fir, 18" dia., bears S.79¾°W., 121.4 ft., with a healed blaze.  
A broken-top lightning-struck living fir, 40" dia., bears N.40¾°W., 10.6 ft with axe marks visible on bark (Orig)  
and a bearing tree mkd. by person(s) unknown  
A fir, 12" dia., bears S.83½°E., 19.7 ft., no marks visible and a bearing tree tag.

Continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor Secs 10, 11, 14, & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

NAD 1983 (2011)  
Latitude: 43°18'49.71" N. Longitude: 122°54'45.90" W.  
From this cor., the BLM Geodetic Control Station No. EC 41166, bears S.83°07'48"E., 190.28 ft., monumented with an aluminum cap, 3¼" dia., cemented in solid bedrock, with top mkd. EC41166 GPS 1992 and a triangle in the center.  
Corner is located in the bottom of a shallow draw, drains S.55°E.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 1/25/2023 - C.S. File 67/55-33  
-----  
Found - 3¼" BLM brass cap (properly mkd) on 2½" pipe up 2" in large rough mound of stone.  
Burnt-dead 12" D.Fir N.55°E., 23.8 ft. healed blaze, add 3½" mag nail right side center.  
Burnt, down 9"x1 ft madrone stump N.72½°E., 48.8 ft, blaze gone.  
Burned-dead 16" D.Fir S.52°E., 32.0 ft. (rec. 31.0 ft) with healed blaze, add 3½" mag nail right side center.  
Burned-dead 18" D.Fir bears (S.79¾°W., 121.4 ft. rec not checked) with healed blaze.  
Burned, hollowed out broke-top lighting struck 40" Fir N.40¾°w., 10.6 ft. marks burned away.  
Burned-dead 12" D.Fir S.83½°E., 20.5 ft. (rec. 19.7 ft) No marks visible, add 3½" mag nail right side center.  
Burned Fir stump S.22¾°E., 65.3 ft.  
Note - Area burnt 9/2020  
Compass decl. 14½°E.  
Lat: 43°18'49.72"N Long: 122°54'45.97"W