



TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From this point, a point reestablished as the ¼ sec. cor. of secs. 10 & 11 by G.R. Lecklider, in 1959, bears S.7°37'30"E., 0.299 chs.; monumented with an iron post, ½" dia., firmly set, projecting 4" above ground, with aluminum cap mkd. Property Corner, from which the BTs mkd. by Lecklider:

A fir, 21" dia., bears N.47¼°E., 23 lks. with healed blaze

A fir, 17" dia., bears N.59°W., 20 lks., with healed blaze

This point is not properly positioned and is not utilized in this survey.

Fd. Ok by R. Quimby 11/2001 - M139-15

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24077)

-----  
The ¼ sec. cor. of secs. 10 and 11, reported by Bedell, Seibold, and Browning in 1992-95, monumented with a stainless steel post, 2½" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd.

from which the BTs reported by Bedell, Seibold, and Browning

A fir, 14" dia., bears N.87¼°E., 15.2 ft., with a healed blaze.

A fir, 24" dia., bears N.41¼°W., 18.5 ft., with a healed blaze.

From this cor., a point erroneously established as the ¼ sec. cor. of secs. 10 & 11, rejected by Bedell, Seibold, and Browning, bears S.7°37'30"E., 19.73 ft.; monumented with an iron post, 5/8" dia. (Record, 1/2" dia.), firmly set, projecting 5" above ground, with an aluminum cap mkd. PROPERTY CORNER; from which the bearing trees reported by Bedell, Seibold, and Browning

A fir, 23" dia., bears N.47¼°E., 15.2 ft., with a healed blaze.

A fir, 21" dia., bears N.59°W., 13.2 ft., with a healed blaze.