

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4203)

-----

Set a post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 2, 3, 10, & 11, marked T26S S2 on NE, R2W S11 on SE, S10 on SW, S3 on NW faces, with 5 notch on S & 2 notches on E edges; from which

- A fir, 12" dia. bears N.35°E., 79 lks. mkd: T26S R2W S2 BT
- A fir, 12" dia., bears S.39°E., 100 lks., mkd: T26S R2W S11 BT.
- A fir, 8" dia. bears S.41°W., 32 lks. mkd: T26S R2W S10 BT
- A willow, 5" dia., bears N.85°W., 58 lks., mkd: T26S R2W S3 BT.

Douglas Co. Surveyors Office - Ben B. Irving, Co. Surveyor - Witnesses: R.L. Irving & Carl Messing - Dec. 5, 1927 - C.S. File 14/31

-----

Location identified OBT N.35°E., 79 lks. which I chop out. Also rotten snag S.50°40'W., 32 lks bearing scribe marks. Set stone "x" 6" chiseled X on top W notches E face 5 notches S face, new BTs:

- 36" fir N.78°35'E., 96 lks.
- 30" fir S.66°20'E., 100 lks. OBT
- 10" fir S.62°30'W., 36 lks.
- 33" fir N.10°15'W., 102 lks.

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12727)

-----

The cor. of secs. 2, 3, 10, & 11, perpetuated & recorded by Irving, in 1927, monumented with a mound of stone, 1½ ft. base, 1 ft. high; from which the only remaining original BT:

- A fir, 57" dia., bears N.35°E., 79 lks., with scribe marks T26 visible on an opened blaze.

and County Surveyor's BTs

- A fir, 36" dia., bears N.78½°E., 96 lks., with a healed blaze.
- A fir, 45" dia., bears S.66½°E., 100 lks. bark scribed T26S R2W S11 CS BT.
- A fir, 17" dia., bears S.62½°W., 36 lks., with a healed blaze.
- A fir, 41" dia., bears N.9½°W., 102 lks., with a healed blaze.

At the corner point

continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor Secs 2, 3, 10, & 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Set an iron post, 28", long. 2½" dia., 24" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T26S R2W  
S 3 | S 2  
S 10 | S 11  
1959

BLM dependent resurvey by Dale T. Bedell & Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Survey Technician, under Group No. 1638, surveyed July 1992/April 1995 - (DCSO records Vol. 51 (Page(s) 19753)

-----  
The cor. of secs. 2, 3, 10, & 11, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, and in a collar of stone, 3 feet dia., with brass cap mkd. from which the remains of an original bearing tree

A decayed fir stump, 63" dia., bears undetermined.35½°E., 79 lks., with fragmentary scribe marks visible on open blaze. (Record, N.35°E.)

and the remains of BTs mkd. by Irving, in 1927

A sawed fir stump, 40" dia., bears N.78½°E., 96 lks., with partially healed blaze.

A fir snag, 47" dia., bears S.66½°E., 100 lks., with healed blaze.

A decayed sawed fir stump, size undetermined, bears S.62½°W., 36 lks., with healed blaze.

A decayed snag, size undetermined, bears N.9½°W., 102 lks., with no marks visible.

and a bearing tree mkd. by person(s) unknown

A fir, 22" dia. bears N.55¼°E., 44½ lks. with healed blaze and new bearing trees

A fir, 7" dia. bears S.10½°E. 30 lks. mkd. T26S R2W S11 BT

A fir, 12" dia., bears S.49½°W., 81½ lks., mkd. T26S R2W S10 BT.

A fir, 8" dia. bears N.59¾°W. 56½ lks. mkd. T26S R2W S3 BT

Fd ok by Ed Monrean 4/2004 C.S. 65/49-38

6/2011: Fd. as per C.S. 65/49-38 by G. Lang, M162-46

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24053-4) (added 9/27/2022)

-----  
The cor. of secs 2, 3, 10, & 11, reported by Bedell, Seibold, & Browning in 1992-95, monumented with an iron post, 2½" dia., firmly set, projecting 12" above ground, in a mound of stone, 3 ft. base, to the top, with brass cap (properly) mkd. Continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor Secs 2, 3, 10, & 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

from which the remains of the bearing trees reported by Bedell, Seibold, and Browning

A decayed fir stump, 63" dia., bears N.35½°E., 52.1 ft., with no marks visible on open blaze. (Original)

A fir stump, 28" dia., bears N.55¼°E., 29.4 ft., with a healed blaze.

A decayed fir stump, 46" dia., bears N.78½°E., 63.4 ft., with a healed blaze.

A fir snag, 46" dia., bears S.66½°E., 66.0 ft., with a healed blaze and scribe marks T2 R2 S visible on bark above the healed blaze.

A fir snag, 13" dia., bears S.10½°E., 19.8 ft., with a healed blaze.

A fir, 26" dia., bears S.49½°W., 53.8 ft., with a healed blaze.

A fir snag, 11" dia., bears N.59¾°W., 37.3 ft., with a healed blaze.

and new bearing trees

A fir, 5" dia., bears S.70°E., 18.9 ft mkd T26S R2W S11 BT

A maple, 9" dia., bears N.48½°W., 22.2 ft., mkd. T26S R2W S3 ST on bark.

No new bearing trees available in sec. 2.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center

NAD 1983 (2011)

Latitude: 43°19'42.06" N. Longitude: 122°54'45.53" W.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 12/7/2021 (Filed 4/11/2022) - C.S. File 67/51-40

Found - 3¾" BLM brass cap

A burnt sawed Fir stump 30"x2½" N.78½°E., 63.4 ft.

Burnt out shell 8' tall S.66½°E., 66.0 ft.

BT by person(s) unknown

29"x8' sawn fir stump N.55¼°E., 29.9 (rec. 29.4) fully healed scar.

BLM BTs 13" Fir burnt snag S.10½°E., 19.6 (Rec. 19.8)

26"x6' sawn fir stump S.49½°W., 54.6 (Rec. 53.8)

~~Unrecorded~~ BLM BT 2018

Double trunk Maple bark scribed T26S R2W S3 BT on 9" southerly trunk N.48½°W., 22.2

New - 5/8" I.Rod inside ¾" I.Pipe North 45.0 on Easterly road shoulder.

Note - Corner is approx 55' south of access road.

Area burnt 9/2020

Compass decl. 14½°E. See sketch in file.

Lat: 43°19'42.17" N Long: 122°54'45.74" W