

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4204-5)

-----

Set post, 3 ft. long, & 3" sq., 24" in the ground for the ¼ sec. cor. marked ¼ S on W face, from which:  
A fir, 5" dia., bears N.21°W., 34 lks., mkd: ¼ S BT.  
A fir, 12" dia., bears N.32°E., 20 lks., mkd: ¼ S BT.

G. Robert Lecklider - For: Mrs. Carl A. Messing - July 6, 1959 - M11-31

-----

Orig. Corner not found.  
Set - 1½" pipe in mound of stone  
22" fir, S.71°W., 9.5 ft.  
10" fir, N.67°E., 10.5 ft.

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12728)

-----

The sec. cor. of secs. 2 & 3, restored at proportionate distance by Lecklider, in 1959, monumented with a 1¾" iron pipe, protruding 16" above ground, firmly set in a mound of stone, 2 ft. base, 1 ft. high, from which:  
A fir, 8" dia., bears N.66½°E., 16 lks. mkd ¼ S2 RE4079 BT  
A fir, 20" dia. bears S.70°W., 14 lks., mkd ¼ S3 RE4079 BT  
At the corner point  
Set an iron post, 28" long 2½" dia., 24" in the ground, & in a mound of stone, 3 ft. base, to top, with brass cap mkd:  
T26S R2W  
¼  
S 3 | S 2  
1959  
Deposit the iron pipe alongside the iron post.

Ed Monrean - April 2004 - C.S. File 65/49-36

-----

Found - 3¾" BLM brass cap on a 2½" iron pipe 0.2 ft. above grade adjoined in the SE quadrant with a 1¾" galvanized iron pipe 0.5 ft. above grade, all in a mound of stone.  
Fir 16" (10") dia., bears N.67°E., 10.5 ft., with healed face & tag.  
Fir 30" (22") dia., bears S.71°W., 9.5 ft., with double healed faces & tag.

continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New -	D.Fir 12" dia., bears N.41°W., 8.1 ft., face scribed "E¼ S3 BT"
	D.Fir 31" dia., bears S.6°W., 19.6 ft., face scribed "E¼ S3 BT"
Note -	Distances to fd. BTs were measured with EDM at approx. side center of root crown. New BTs were measured to a spike set at approx. side center. Trees were red band & face painted. Trees fd. without tags have new tags facing monument.

6/2011: Fd. as per C.S. 65/49-36 by G. Lang, M162-46

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24054)

-----

The ¼ sec. cor. of secs. 2 & 3, reported by Zirpel, Jr., and Glenn in 1959; perpetuated by Monrean, in 2004; monumented with an iron post, 2½" dia., firmly set, projecting 1" above ground, in a collar of stone, (alongside is an iron pipe, 1½" dia. [(Record, 1¾" dia., firmly set, projecting 7") with a brass cap (properly) mkd.

from which the BTs reported by Zirpel, Jr., and Glenn

- A fir, 21" dia., bears N.66½°E., 10.6 ft., with a healed blaze.
- A fir, 32" dia., bears S.70°W., 9.2 ft., with a healed blaze.

and the BTs mkd. by Monrean

- A fir, 36" dia., bears S.5½°W., 20.0 ft., with a healed double blaze.
- A fir, 13" dia., bears N.46°W., 8.3 ft., with a healed double blaze.