

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec Cor for 2 & 3 only, (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 9 Page(s) 3581)

-----  
Set Cedar post 4 ft. long, 4" sq., with marked stone 12" in the ground, for corner to secs. 2, 3, 34 and 35, mkd. T25S S35 on NE.; R2W S2 on SE.; T26S S3 on SW.; S34 on NW faces with 4 notches on W. and 2 notches on E. edges, and raised mound of stone 2 ft. high, 4½ ft. base around post.

GL0 survey by C.M. Collier, Deputy Surveyor, under Instructions dated May/Sept. 1913 - (DCSO records Vol. 10 Page(s) 4269 and 4273)

-----  
(Page 4269)  
Search diligently but find no trace of sec. cor. markings. Set temp. cor. for secs. 2 and 3.  
(Page 4273)  
Set a basalt stone 16x10x7 ins., 10" in the ground for cor. of secs. 2 and 3 only, marked with 2 notches on the E. and 4 notches on the W. edges; from which  
    A rock in place, 3½ ft. x 4 ft. x 3 ft. high, bears S.20°E., 54 lks. dist. mkd. on NW. face; T26S R2W S2 B0  
    A Fir 14" dia., bears S.82°30'W., 256 lks. dist. mkd. T26S R2W S3 BT.  
Illick's cabin bears S.4°30'W., about 20 chs.  
Soper's Point bears S.68°E., about 22 chs.

Survey by G. Robert Lecklider - For: Mrs. Carl A. Messing - July 6, 1959 - M 11-31

-----  
Found - Corner Stone.  
    3.5 ft. x 4 ft. x 3 ft. rock, S.20°E., 54 lks.  
    42" Fir, S.82°30'W., 256 lks., rescribed.  
New BT - 38" Fir, S.45°E., 37.5 ft.

BLM Resurvey by Irving Zirpel & Wm. Glenn, under Group #404, Surveyed May/Oct. 1959 (DCSO rec. Vol. 30 Pgs. 12718-19)

-----  
The cor. of secs. 2 & 3 only, monumented by Collier in 1913 with a basalt stone, 16x10x7 ins., firmly set, with 2 notches on the E. and 4 notches on the W. edge, from which Collier's 1913 bearing object and bearing tree:  
    A basalt stone 4 x 3½ x 3 ft. above ground, bears S.20°E., 54 lks. dist. mkd. T26S R2W S2 BS on NW. face.  
    A Fir 40" dia., bears S.82½°W., 248½ lks. dist. with a healed blaze. This tree has been re-blazed in 1959  
(Cont. Next Page)

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec Cor for 2 & 3 only, (North)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

above the healed blaze and scribed S3 T26S R2W RE4079.  
(Rec. dist. 256 lks.)

and a locally established bearing tree mkd. in 1959:

A Fir 33" dia., bears S.44½°E., 56 lks. dist. mkd. S2 T26S  
R2W RE4079 BT on unhealed blaze.

At the corner point

Set an iron post, 28" long, 2 ½" dia., 26" in the ground,  
with brass cap mkd:

T 25 S R 2 W  
    S 35  
    S 3 | S 2  
T 26 S R 2 W  
    1959

Deposit the original corner stone alongside the iron post.

Fd. Corner OK and used in Cadastral Survey by Berry, Wofford,  
Popken and Glenn Baughman R.L.S. #536, surveyed July  
1972/oct. 1975 - (DCSO records Vol. 36 Page(s) 15100)

Fd. & used on BLM dependent resurvey by Bryan S. Seibold,  
Cadastral Surveyor and Robert H. Browning, Survey Technician,  
under Group #1754, surveyed May 1995 - July 1998 - (DCSO  
records Vol. 53 Page(s) 20449-50)

Ed Monrean - April 2004 - C.S. File 65/49-35

Found - ¾" BLM brass cap on 2½" iron pipe 0.5 ft. above  
grade with stone adjacent in SE quadrant.

Fir 56" (42") dia., bears S.82°30'W., (164.0) 169.0  
ft., with healed face.

Fir 52" (38") dia., bears S.44°30'E., (S.45°E.) 37.5  
(37.0) ft., with healed face & tag.

4'x3' rock bears S.20°E., 37.6 (35.6) ft. to approx.  
center, with top (part with scribing) apparently  
broken off by tractor work.

New - D.Fir 17" dia., bears N.40°W., 14.2 ft. Face scribed  
"T25S R2W S35 BT"

D.Fir 23" dia., bears S.1°W., 50.1 ft. Face scribed  
"T26S R2W S23 BT"

Note - Distances to fd. BTs were measured with EDM at  
approx. side center of root crown. New BTs were  
measured to a spike set at approx. side center.  
Trees were red band & face painted. Trees fd.  
without tags have new tags facing monument.

continued next page

PRIMARY CORNER DESCRIPTION Sec Cor for 2 & 3 only, (North)

Alias	Description

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2317, Surveyed June 2010/June 2011 - DCSO records Vol. 57 Page(s) 22786-7

-----  
The cor. of sec. 2 & 3 only, T26S R2W perpetuated by Monrean, in 2004, monumented with an iron post, 2½" dia., firmly set, projecting 4" above the ground, with brass cap (properly) mkd from which accessories mkd. by Collier  
A rock in place, 3½x4x3 ft. high, bears S.20°E., 35.6 ft., with an S chiseled in the NW face.  
A fir, 58" dia., bears S.83½°W., 165.0 ft., with a healed blaze.  
and a bearing tree mkd. by Lecklider, in 1959  
A fir, 55" dia., bears S.44½°E., 37.0 ft., with a healed blaze.  
and bearing trees mkd. by Monrean  
A fir, 27" dia., bears S.1¼°E., 50.6 ft., with fragmentary scribe marks visible on a partially healed blaze.  
A fir, 19" dia., bears N.43¾°W., 14.2 ft., with fragmentary scribe marks visible on a partially healed blaze.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24054-5)

-----  
The cor. of secs. 2 and 3, on the N. bdy. of the Tp., reported by Skeesick in 2010-11, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd. from which the remains of the BTs reported by Skeesick  
A fir stump, 55" dia., bears S.44½°E., 37.0 ft., with a healed blaze.  
A rock in place, 3½x4x3 ft. high, bears S.20°E., 35.6 ft., with an S chiseled on NW face.  
A fir, 29" dia., bears S.1¼°E., 50.6 ft., with a healed blaze.  
A fir, 57" dia., bears S.83½°W., 165.0 ft., with a healed blaze.  
A fir, 19" dia., bears N.43¾°W., 14.2 ft., with illegible scribe marks visible on partially healed blaze.  
The basalt stone, 16x10x7", established by Collier in 1913-14, mkd. with 2 notches on east and 4 notches on west faces, was found set alongside the cor. Bury the stone alongside the cor.  
Note: The cor. was incorrectly identified as an original cor. on the Skeesick and the Seibold & Browning 1995-98 plats.