

PRIMARY CORNER DESCRIPTION Closing Corner to Secs. 34 & 35

Alias _____	Description <u>Cor. 2 Tract 38</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. N. Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Page(s) 4224-5)

Set granite stone, 8x10x14", 10" in the ground for cor. secs. 26, 27, 34, & 35, marked with 2 notches on E & 1 notch on S edge; from which

- A cedar, 12" dia., bears N.82°E., 51 lks., mkd: T26S R2W S26 BT.
- A fir, 12" dia., bears S.33°W., 104 lks., mkd: T26S R2W S35 BT.
- A cedar, 6" dia., bears S.85°W., 37 lks., mkd: T26S R2W S34 BT.
- A cedar, 14" dia., bears N.31°W., 151 lks., mkd: T26S R2W S27 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4307, 4311 & 4342)

Pg 4307

The cor. established by Deputy Gibb in 1909 as the cor. of secs. 26, 27, 34 & 35, which is a granite stone, 4x10x8" above ground, firmly set, marked & witnessed as described by the surveyor general.

I destroy the cor. set in the rejected revision survey as the cor. of secs. 26, 27, 34, & 35 & marks on BTs.

Pg 4311

Intersect S bdy of sec. 27, 7.19 chs. E of SW cor. of sec. 26
At the point of intersection

Set an iron post, 3 ft. long, 1" dia., 24" in the ground, for closing cor. of secs. 34 & 35, with brass cap marked:

```

T26S R2W
  S 26
-----
S 34 | S 35
T26S R2W
  CC
  1916

```

from which

- A cedar, 10" dia., bears S.15°E., 43 lks., mkd: T26S R2W S35 BT.
- A fir, 20" dia. bears S.38°W. 21 lks. mkd: T26S R2W S34 BT

Pg 4342

Intersect the closing cor. of secs. 34 & 35. I now place additional marks on this post to designate it as cor. 2 of Tract 38. The post is now marked
continued next page

PRIMARY CORNER DESCRIPTION Closing Corner to Secs. 34 & 35

Alias _____	Description <u>Cor. 2 Tract 38</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>T26S R2W <u>S 26</u> S 34 S 35 T26S R2W 2 TR 38 CC 1916</p>														
<p>Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - D. West - July 1967 - C.S. File 54/40-24</p> <p>-----</p> <p>(This is also the #2 corner of Tract 38) Found - 1916 GLO brass cap, firmly set & properly marked. SW BT is completely destroyed. Find reverse scribe o the SE BTs fragments. New BTs- 4" Cedar S.23°E., 16.5 ft. mkd: CC S35 CS BT 14" Yew N.51°E., 22.3 ft. mkd: CC CS BT No trees avail. in sec. 34 This corner lies on E slope approx 140 ft W of small creek</p>														
<p>BLM dependent resurvey by Dale T. Bedell & Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Survey Technician, under Group No. 1638, surveyed July 1992/April 1995 - (DCSO records Vol. 51 (Page(s) 19749)</p> <p>-----</p> <p>The closing cor. of secs. 34 & 35, on the S. bdy. of sec. 26, identical with cor. No. 2 of Tract 38, perpetuated by Tracy, in 1967, utilized by Shrum, in 1979; monumented with an iron post, 1" dia., firmly set, projecting 12" above the ground, with brass cap mkd. T26S R2W S26 S34 S35 T26S R2W 2 TR38 CC 1916, from which the remains of an original bearing tree: A cedar rootcrown, size indeterminate, bears S.23°E., 43 lks., no marks visible. (Record, S.15°E.) and bearing trees mkd. by Tracy A yew, 18" dia. bears N.51°E., 34 lks. with scribe marks CS visible on a partially healed blaze. A cedar, 10" dia., bears S.23°E. 25 lks. with healed blaze and a new bearing tree A fir, 6" dia. bears S.35°W., 4½ lks. mkd. T26S R2W S34 BT This corner was fixed in position as cor. No. 2 of Tract 38, during the 1918 Tract survey by Fred Mensch. The marks CC were removed and add the marks BLM 1994 to the brass cap, now mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T26S R2W</td> </tr> <tr> <td colspan="2" style="text-align: center;"><u>S 26</u></td> </tr> <tr> <td style="text-align: center;">T26S</td> <td style="text-align: center;">R2W</td> </tr> <tr> <td style="text-align: center;">S 34</td> <td style="text-align: center;">S 35</td> </tr> <tr> <td colspan="2" style="text-align: center;">2 TR 38</td> </tr> <tr> <td colspan="2" style="text-align: center;">BLM 1994</td> </tr> <tr> <td colspan="2" style="text-align: center;">1916</td> </tr> </table> <p style="text-align: right;">continued next page</p>	T26S R2W		<u>S 26</u>		T26S	R2W	S 34	S 35	2 TR 38		BLM 1994		1916	
T26S R2W														
<u>S 26</u>														
T26S	R2W													
S 34	S 35													
2 TR 38														
BLM 1994														
1916														

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 507200

PRIMARY CORNER DESCRIPTION Closing Corner to Secs. 34 & 35

Alias _____ Description Cor. 2 Tract 38

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

From this corner, the SW. cor. of sec. 26 bears
S.89°23'00"W., 7.215 chs.