

PRIMARY CORNER DESCRIPTION C-W 1/16 Sec 2

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

G.R. Lecklider - For: Carl Messing - June 1959 - M11-31 ----- Set - R.R. spike in rock 24" Fir, N.66°E., 19.7 ft. 28" Fir, N.00°E., 23.0 ft.	
Ed Monrean, ie engineering - For: Roseburg Resources Co. - April 2004 - M144-47 & C.S. File 65/49-34C ----- Found - R.R. spike in rock w/ BTs 28" Rotten Fir stump, bears N.7°W., (North) 23.0', with visible scribing C 1/16 S2 beside R 4079" 19" (24") bark-less rotten fir stump, bears N.61°E., (N.66°E.) 19.2' (19.7') with visible scribing "WC 1/16 S2 Beside R 4079" New - 9" D.Fir bears S.5°W., 6.8' face scribed "CWC 1/16 S2 BT" 9" D.Fir bears S.74°E., 27.9' face scribed "CWC 1/16 S2 BT" Note - Distances to fd BTs were measured with EDM at approx. side center of root crown. New BTs were measured to a spike set at approx. side center. Trees were red band and face painted. Trees fd without tags have new tags facing monument. Decl. 19°E	
Fd. RR spike, Greg Lang, 7/2011 - M162-46	
Ken Hoffine, Lone Rock Timber - Crew: W. Addington, D. Saily, Gary Angiolet - 12/2016 - C.S. File 65/93-63 ----- Found - 28" rotten Fir stump bears N.5°W., 22.7 FT. (REC N.7°W., 23.0 FT.) destroyed during landing construction. 19" Rotten Fir stump bears N.61½°E., 18.9 FT. (rec. N.61°E., 19.2 ft.) destroyed during construction. 11" D.Fir bears S.74°E., 27.85 ft. (rec: S.74°E., 27.9 FT.) DESTROYED DURING LANDING CONSTRUCTION. 12" D.Fir bears S.6°W., 7.0 ft. (rec. S.5°W. 6.8 ft) destroyed during landing construction. Monument- CW 1/16 SEC 2 monument RR Spike per Lecklider map M11-31 (Not fd. destroyed during construction.) Reset monument with 5/8" iron rod with Yellow plastic cap marked: LONE ROCK TIMBER PLS 2291 From accessories. New corner monument is buried under 2 ft. of large rocks.	
Continued next page	

PRIMARY CORNER DESCRIPTION C-W 1/16 Sec. 2

Alias	Description

- New - PK nail in southerly end of large rock outcropping bears S.69°43'W., 37.23 FT.
- PK nail in middle of large rock outcropping bears N.46°46'W., 55.03 fr.
- Set 5/8" iron rod with orange plastic cap marked: LONE ROCK TIMBER PLS 2291 BEARS S.88°15'E., 200.55 FT.
- Set 5/8" iron rod with orange plastic cap marked: LONE ROCK TIMBER PLS 2291 bears N.74°16'E., 184.28 ft.
- A 24"x12" tall D.Fir stump with 8" mag hub at center bears S.38°38'E., 61.95 ft.
- A 36" D.Fir tree bears S.5½°E., 42.45 ft. we scribed S 2 CW 1/16 BT and tagged the tree.
- A 32" D.Fir tree bears S.65°E., 130.14 ft. we scribed S 2 CW 1/16 BT and tagged the tree.

Note - Record corner monument was a RR spike and is buried under several feet of rock fill in a logging landing constructed in 2016. in the construction of the landing area record BTs were destroyed. We were unsuccessful in relocating the railroad spike with a magnetic pin finder. Using existing reference accessories we established prior to construction west and east of the corner location we set a new 5/8" iron rod CW 1/16 monument with a yellow plastic cap. Future logging operations will likely disturb or destroy accessories to the west of the corner location. We placed 2 ft. of rock on top of the new monument to protect the corner from further disturbment.
Bearing basis: record bearing tree from CW 1/16 at S.74°E., previously tied.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24070-1)

The CW1/16 sec. cor. of sec. 2, established by Lecklider, in June, 1959; perpetuated by Hoffine, in 2016; and is accepted as the cor.; monumented with an iron rod, 5/8" dia., firmly set, with top 24" below the surface of the ground, on the west edge of a rocky logging landing, with an orange plastic cap mkd. LONE ROCK TIMBER LS 2291, from which the remains of the bearing trees mkd. by Lecklider

- A fir, 32" dia., bears S.66¾°E., 130.3 ft., with scribe marks CW1/16 BT S2 visible on partially healed blaze.
- A fir stump, 26" dia., bears S.40½°E., 61.9 ft., no marks visible.

Continued next page

PRIMARY CORNER DESCRIPTION C-W 1/16 Sec. 2

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A fir, 33" dia., bears S.7°E., 42.6 ft., with scribe marks CW1/16 BT S2 visible on partially healed blaze. and the bearing objects mkd. by Hoffine

An iron rod, 5/8" dia., firmly set, projecting 3" above ground, bears N.72°16'44"E., 184.20 ft., with an orange plastic cap mkd. LONE ROCK TIMBER LS 2291.

An iron rod, 5/8" dia., firmly set, projecting 7" above ground, bears N.89°47'12"E., 200.47 ft., with an orange plastic cap mkd. LONE ROCK TIMBER LS 2291.

A PK Nail, in the southerly end of a large rock outcropping, bears S.67°46'50"W., 37.36 ft.

At the corner point
 Set a stainless steel post, 28" long, 2½" dia., 22" in the ground, directly over the iron rod, in a large supporting mound of stone, to the top, with brass cap mkd.

W 1/16
 C-----C
 S2
 2019

Corner is located W, 125 ft., of an intersection of three graveled roads, each 16' wide, bear S.70°E. S.45°W. & N.10°W.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 2/2/2022 (filed 11/23/2022) - C.S. File 67/55-10

Found - 3¼" brass cap fd out of position 10' westerly on surface down rocky slope, reset over iron rod, add marks reset 2022

Burnt-dead, 33" D.Fir S.66¾°E., 130.5 ft (rec. 130.3 ft.) burnt blaze, add 3½" mag nail rt side center

A sawn 26"x1½" ft fir stump S.40½°E., 61.9 ft. (rec. S.38°38'E., 61.95 ft) mag nail top center.

Sawn 33"x3 ft. fir stump S.7°E., 42.6 ft. (Rec. S.5½°E., 42.45 ft) blaze burnt add 3½" mag nail top center.

5/8" iron rod N.72°16'44"E., 184.2 ft. (rec. N.74°16'E., 184.28 ft.) orange plastic cap Lone Rock Timber LS 2291 up 3"

5/8" iron rod N.89°47'12"E., 200.47 ft. (rec S.88°15'E., 200.55 ft) orange plastic cap Lone Rock Timber LS 2291 up 7"

New - 5/8" iron rod inside 3/4" iron pipe S.88°E., 40.6 ft. up 6" in rough mound of stone.

5/8" iron rod N.41¾°E., 46.0 ft with yellow DCS0 plastic cap up 4" in rough mound of stone.

5/8" iron rod S.34½°E., 42.8 ft. with yellow DCS0 plastic cap up 6" in rough mound of stone.

Continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 520640

PRIMARY CORNER DESCRIPTION C-W 1/16 Sec. 2

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Note - Area burnt 9/20/2020
Compass decl. $14\frac{1}{2}^{\circ}$ E.
Corner is west 125' of road intersection of 3 roads,
each 16' wide bears S.70°E., S.45°W., and N.10°W.
Lat: $43^{\circ}20'09.83''$ N Long: $122^{\circ}54'27.37''$ W.